



|  |   |
|--|---|
| <b>Disposal</b>                                  | Dispose of contents/container in accordance with local/regional/national/international regulations. |
| <b>Hazard(s) not otherwise classified (HNOC)</b> | None known.   |
| <b>Supplemental information</b>                  | None.   |

### 3. Composition/information on ingredients

#### Mixtures

| Chemical name                                    | Common name and synonyms | CAS number | %         |
|--|--------------------------|------------|-----------|
| PCBTf, P-Chlorobenzotrifluoride                  |                          | 98-56-6    | 40 - < 50 |
| TITANIUM DIOXIDE                                 |                          | 13463-67-7 | 10 - < 20 |
| CALCIUM CARBONATE, LIMESTONE                     |                          | 1317-65-3  | 1 - < 3   |
| SILICA   |                          | 7631-86-9  | 1 - < 3   |
| BIS(1,2,2,6,6-PENTAMETHYL-4-PIPERIDINYL)SEBACATE |                          | 41556-26-7 | < 1       |
| ETHYLBENZENE                                     |                          | 100-41-4   | < 1       |
| NAPHTHA (PETROLEUM), HYDROSULFURIZED HEAVY       |                          | 64742-82-1 | < 1       |
| STYRENE MONOMER                                  |                          | 100-42-5   | < 0.2     |

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

### 4. First-aid measures

|   |  |
|---|--|
| <b>Inhalation</b>   | Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.  |
| <b>Skin contact</b>   | Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema or other skin disorders: Seek medical attention and take along these instructions.   |
| <b>Eye contact</b>  | Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Get medical attention if irritation develops and persists.  |
| <b>Ingestion</b>  | Rinse mouth. Get medical attention if symptoms occur.  |
| <b>Most important symptoms/effects, acute and delayed</b>                     | May cause drowsiness and dizziness. Headache. Nausea, vomiting. Direct contact with eyes may cause temporary irritation. May cause respiratory irritation. May cause an allergic skin reaction. Dermatitis. Rash.  |
| <b>Indication of immediate medical attention and special treatment needed</b> | Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.  |
| <b>General information</b>  | Take off all contaminated clothing immediately. IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse. |

### 5. Fire-fighting measures

|  |  |
|--|--|
| <b>Suitable extinguishing media</b>                                  | Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).  |
| <b>Unsuitable extinguishing media</b>                                | Do not use water jet as an extinguisher, as this will spread the fire.   |
| <b>Specific hazards arising from the chemical</b>                    | Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed. |
| <b>Special protective equipment and precautions for firefighters</b> | Self-contained breathing apparatus and full protective clothing must be worn in case of fire.  |
| <b>Fire fighting equipment/instructions</b>                          | In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.   |
| <b>Specific methods</b>  | Use standard firefighting procedures and consider the hazards of other involved materials.   |
| <b>General fire hazards</b>  | Flammable liquid and vapor.  |

## 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

### Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Take precautionary measures against static discharge. Use only non-sparking tools. Keep combustibles (wood, paper, oil, etc.) away from spilled material.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground.

### Environmental precautions

## 7. Handling and storage

### Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid breathing mist or vapor. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

### Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

## 8. Exposure controls/personal protection

### Occupational exposure limits

#### US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

| Components                                   | Type | Value                 | Form                 |
|--|------|-----------------------|----------------------|
| CALCIUM CARBONATE, LIMESTONE (CAS 1317-65-3) | PEL  | 5 mg/m3               | Respirable fraction. |
| ETHYLBENZENE (CAS 100-41-4)                  | PEL  | 15 mg/m3<br>435 mg/m3 | Total dust.          |
| TITANIUM DIOXIDE (CAS 13463-67-7)            | PEL  | 100 ppm<br>15 mg/m3   | Total dust.          |

#### US. OSHA Table Z-2 (29 CFR 1910.1000)

| Components                     | Type    | Value   |
|--------------------------------|---------|---------|
| STYRENE MONOMER (CAS 100-42-5) | Ceiling | 200 ppm |
|                                | TWA     | 100 ppm |

#### US. OSHA Table Z-3 (29 CFR 1910.1000)

| Components             | Type | Value                 |
|------------------------|------|-----------------------|
| SILICA (CAS 7631-86-9) | TWA  | 0.8 mg/m3<br>20 mppcf |

**US. ACGIH Threshold Limit Values**

| Components  | Type | Value    |
|---|------|----------|
| ETHYLBENZENE (CAS 100-41-4)                                 | TWA  | 20 ppm   |
| NAPHTHA (PETROLEUM), HYDROSULFURIZED HEAVY (CAS 64742-82-1) | TWA  | 100 ppm  |
| STYRENE MONOMER (CAS 100-42-5)                              | STEL | 40 ppm   |
|   | TWA  | 20 ppm   |
| TITANIUM DIOXIDE (CAS 13463-67-7)                           | TWA  | 10 mg/m3 |

**US. NIOSH: Pocket Guide to Chemical Hazards**

| Components  | Type    | Value      | Form        |
|---|---------|------------|-------------|
| CALCIUM CARBONATE, LIMESTONE (CAS 1317-65-3)                | TWA     | 5 mg/m3    | Respirable. |
|   |         | 10 mg/m3   | Total       |
| ETHYLBENZENE (CAS 100-41-4)                                 | STEL    | 545 mg/m3  |             |
|   |         | 125 ppm    |             |
|   | TWA     | 435 mg/m3  |             |
|   |         | 100 ppm    |             |
| NAPHTHA (PETROLEUM), HYDROSULFURIZED HEAVY (CAS 64742-82-1) | Ceiling | 1800 mg/m3 |             |
| SILICA (CAS 7631-86-9)                                      | TWA     | 6 mg/m3    |             |
| STYRENE MONOMER (CAS 100-42-5)                              | STEL    | 425 mg/m3  |             |
|   |         | 100 ppm    |             |
|   | TWA     | 215 mg/m3  |             |
|   |         | 50 ppm     |             |

**Biological limit values****ACGIH Biological Exposure Indices**

| Components                     | Value    | Determinant                                   | Specimen            | Sampling Time |
|--------------------------------|----------|---|---------------------|---------------|
| ETHYLBENZENE (CAS 100-41-4)    | 0.15 g/g | Sum of mandelic acid and phenylglyoxylic acid | Creatinine in urine | *             |
| STYRENE MONOMER (CAS 100-42-5) | 400 mg/g | Mandelic acid plus phenylglyoxylic acid       | Creatinine in urine | *             |
|                                | 0.2 mg/l | Styrene                                       | Venous blood        | *             |

\* - For sampling details, please see the source document.

**Exposure guidelines****US - California OELs: Skin designation**

STYRENE MONOMER (CAS 100-42-5)

Can be absorbed through the skin.

**US - Minnesota Haz Subs: Skin designation applies**

STYRENE MONOMER (CAS 100-42-5)

Skin designation applies.

**Appropriate engineering controls**

Explosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

**Individual protection measures, such as personal protective equipment****Eye/face protection**

Chemical respirator with organic vapor cartridge and full facepiece.

|                                       |   |
|---------------------------------------|---|
| <b>Skin protection</b>                |   |
| <b>Hand protection</b>                | Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier.   |
| <b>Other</b>                          | Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.  |
| <b>Respiratory protection</b>         | Chemical respirator with organic vapor cartridge and full facepiece.  |
| <b>Thermal hazards</b>                | Wear appropriate thermal protective clothing, when necessary.   |
| <b>General hygiene considerations</b> | When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace. |

## 9. Physical and chemical properties

### Appearance

|  |                              |
|--|------------------------------|
| <b>Physical state</b>                          | Liquid.                      |
| <b>Form</b>                                    | Liquid.                      |
| <b>Color</b>                                   | White.                       |
| <b>Odor</b>                                    | Mild.                        |
| <b>Odor threshold</b>                          | Not available.               |
| <b>pH</b>                                      | Not available.               |
| <b>Melting point/freezing point</b>            | -32.8 °F (-36 °C) estimated  |
| <b>Initial boiling point and boiling range</b> | 282 °F (138.89 °C) estimated |
| <b>Flash point</b>                             | 109.0 °F (42.8 °C) estimated |
| <b>Evaporation rate</b>                        | Not available.               |
| <b>Flammability (solid, gas)</b>               | Not applicable.              |

### Upper/lower flammability or explosive limits

|  |                    |
|--|--------------------|
| <b>Flammability limit - lower (%)</b>          | Not available.     |
| <b>Flammability limit - upper (%)</b>          | Not available.     |
| <b>Explosive limit - lower (%)</b>             | Not available.     |
| <b>Explosive limit - upper (%)</b>             | Not available.     |
| <b>Vapor pressure</b>                          | 8.62 hPa estimated |
| <b>Vapor density</b>                           | Not available.     |
| <b>Relative density</b>                        | Not available.     |
| <b>Solubility(ies)</b>                         |                    |
| <b>Solubility (water)</b>                      | Not available.     |
| <b>Partition coefficient (n-octanol/water)</b> | Not available.     |
| <b>Auto-ignition temperature</b>               | Not available.     |
| <b>Decomposition temperature</b>               | Not available.     |
| <b>Viscosity</b>                               | Not available.     |

### Other information

|                             |   |
|-----------------------------|---|
| <b>Density</b>              | 12.63 lbs/gal   |
| <b>Explosive properties</b> | Not explosive.  |
| <b>Flammability class</b>   | Combustible II estimated  |
| <b>Oxidizing properties</b> | Not oxidizing.  |
| <b>Percent volatile</b>     | 51 % estimated  |
| <b>Specific gravity</b>     | 1.52  |
| <b>VOC</b>                  | 0.86 lbs/gal (103.53 g/l) Coating VOC<br>0.39 lbs/gal (47.20 g/l) Material VOC<br>0.69 lbs/gal (82.38 g/l) Coating VOC as applied<br>0.32 lbs/gal (37.76 g/l) Material VOC as applied |

## 10. Stability and reactivity

|   |  |
|---|--|
| <b>Reactivity</b>                         | The product is stable and non-reactive under normal conditions of use, storage and transport.  |
| <b>Chemical stability</b>                 | Material is stable under normal conditions.  |
| <b>Possibility of hazardous reactions</b> | Hazardous polymerization does not occur.   |
| <b>Conditions to avoid</b>                | Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials. |
| <b>Incompatible materials</b>             | Strong oxidizing agents.   |
| <b>Hazardous decomposition products</b>   | No hazardous decomposition products are known.   |

## 11. Toxicological information

### Information on likely routes of exposure

|                     |  |
|---------------------|--|
| <b>Inhalation</b>   | May cause drowsiness and dizziness. Headache. Nausea, vomiting. May cause irritation to the respiratory system. Prolonged inhalation may be harmful. |
| <b>Skin contact</b> | May cause an allergic skin reaction.   |
| <b>Eye contact</b>  | Direct contact with eyes may cause temporary irritation.   |
| <b>Ingestion</b>    | Expected to be a low ingestion hazard.   |

**Symptoms related to the physical, chemical and toxicological characteristics** Headache. May cause drowsiness and dizziness. Nausea, vomiting. May cause respiratory irritation. May cause an allergic skin reaction. Dermatitis. Rash.

### Information on toxicological effects

**Acute toxicity** Narcotic effects. May cause an allergic skin reaction. May cause respiratory irritation.

| <b>Components</b>   | <b>Species</b> | <b>Test Results</b>                                   |
|---|----------------|---|
| ETHYLBENZENE (CAS 100-41-4)                                 |                |   |
| <b>Acute</b>  |                |   |
| <b>Dermal</b>   |                |   |
| LD50  | Rabbit         | 17800 mg/kg   |
| <b>Oral</b>   |                |   |
| LD50  | Rat            | 3500 mg/kg  |
| NAPHTHA (PETROLEUM), HYDROSULFURIZED HEAVY (CAS 64742-82-1) |                |   |
| <b>Acute</b>  |                |   |
| <b>Inhalation</b>   |                |   |
| LC50  | Rat            | 61 mg/l, 4 Hours                                      |
| <b>Oral</b>   |                |   |
| LD50  | Rat            | > 25 ml/kg  |
| PCBTf, P-Chlorobenzotrifluoride (CAS 98-56-6)               |                |   |
| <b>Acute</b>  |                |   |
| <b>Dermal</b>   |                |   |
| LD50  | Rabbit         | > 2000 mg/kg  |
| <b>Inhalation</b>   |                |   |
| LC50  | Rat            | 4468 ppm, 4 hours (vapor)<br>33 mg/l, 4 hours (vapor) |
| <b>Oral</b>   |                |   |
| LD50  | Rat            | 13000 mg/kg   |
| SILICA (CAS 7631-86-9)                                      |                |   |
| <b>Acute</b>  |                |   |
| <b>Oral</b>   |                |   |
| LD50  | Mouse          | > 15000 mg/kg   |
|   | Rat            | > 22500 mg/kg   |

| Components                     | Species | Test Results      |
|--------------------------------|---------|-------------------|
| STYRENE MONOMER (CAS 100-42-5) |         |                   |
| <b>Acute</b>                   |         |                   |
| <b>Inhalation</b>              |         |                   |
| LC50                           | Mouse   | 4940 ppm, 2 Hours |
|                                | Rat     | 2770 ppm, 4 Hours |
|                                |         | 24 mg/l, 4 Hours  |
| <b>Oral</b>                    |         |                   |
| LD50                           | Mouse   | 316 mg/kg         |
|                                | Rat     | 1 g/kg            |

\* Estimates for product may be based on additional component data not shown.

|  |  |
|--|--|
| <b>Skin corrosion/irritation</b>         | Prolonged skin contact may cause temporary irritation.   |
| <b>Serious eye damage/eye irritation</b> | Direct contact with eyes may cause temporary irritation. |
| <b>Respiratory or skin sensitization</b> |  |
| <b>Respiratory sensitization</b>         | Not a respiratory sensitizer.                            |
| <b>Skin sensitization</b>                | May cause an allergic skin reaction.                     |
| <b>Germ cell mutagenicity</b>            | May cause genetic defects.                               |
| <b>Carcinogenicity</b>                   | May cause cancer.  |

#### IARC Monographs. Overall Evaluation of Carcinogenicity

|   |   |
|---|---|
| ETHYLBENZENE (CAS 100-41-4)                                 | 2B Possibly carcinogenic to humans.                 |
| NAPHTHA (PETROLEUM), HYDROSULFURIZED HEAVY (CAS 64742-82-1) | 3 Not classifiable as to carcinogenicity to humans. |
| SILICA (CAS 7631-86-9)                                      | 3 Not classifiable as to carcinogenicity to humans. |
| STYRENE MONOMER (CAS 100-42-5)                              | 2B Possibly carcinogenic to humans.                 |
| TITANIUM DIOXIDE (CAS 13463-67-7)                           | 2B Possibly carcinogenic to humans.                 |

#### OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

#### US. National Toxicology Program (NTP) Report on Carcinogens

|                                |  |
|--------------------------------|--|
| STYRENE MONOMER (CAS 100-42-5) | Reasonably Anticipated to be a Human Carcinogen. |
|--------------------------------|--|

|   |  |
|---|--|
| <b>Reproductive toxicity</b>                              | Suspected of damaging the unborn child.  |
| <b>Specific target organ toxicity - single exposure</b>   | May cause respiratory irritation. May cause drowsiness and dizziness.              |
| <b>Specific target organ toxicity - repeated exposure</b> | Not classified.  |
| <b>Aspiration hazard</b>                                  | Not an aspiration hazard.  |
| <b>Chronic effects</b>                                    | Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects. |

## 12. Ecological information

**Ecotoxicity** The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

| Product   | Species | Test Results   |
|---|---------|--|
| DECADE SELF-PRIMING URETHANE - WHITE/WHITE BASE |         |  |
| <b>Aquatic</b>                                  |         |  |
| Fish  | LC50    | Fish 3.5343 mg/l, 96 hours estimated                         |
| <i>Acute</i>                                    |         |  |
| Crustacea                                       | EC50    | Daphnia 4.1858 mg/l, 48 hours estimated                      |
| <b>Components</b>                               |         |  |
| <b>Species</b>                                  |         |  |
| <b>Test Results</b>                             |         |  |
| ETHYLBENZENE (CAS 100-41-4)                     |         |  |
| <b>Aquatic</b>                                  |         |  |
| Crustacea                                       | EC50    | Water flea (Daphnia magna) 1.37 - 4.4 mg/l, 48 hours         |
| Fish  | LC50    | Fathead minnow (Pimephales promelas) 7.5 - 11 mg/l, 96 hours |

| Components   | Species | Test Results   |
|--|---------|--|
| <b>NAPHTHA (PETROLEUM), HYDROSULFURIZED HEAVY (CAS 64742-82-1)</b> |         |  |
| <b>Aquatic</b>   |         |  |
| Crustacea  | EC50    | Water flea (Daphnia pulex) 2.7 - 5.1 mg/l, 48 hours                    |
| Fish   | LC50    | Rainbow trout,donaldson trout (Oncorhynchus mykiss) 8.8 mg/l, 96 hours |
|  |         | 8.8 mg/l, 96 hours   |
| <b>PCBTF, P-Chlorobenzotrifluoride (CAS 98-56-6)</b>               |         |  |
| <b>Aquatic</b>   |         |  |
| <i>Acute</i>   |         |  |
| Algae  | EC50    | Green algae (Chlamydomonas variabilis) > 0.41 mg/l, 72 hours           |
| Crustacea  | EC50    | Daphnia magna 2 mg/l, 48 hours   |
| Fish   | EC50    | Zebra danio (Danio rerio) 3 mg/l, 96 hours                             |
| <i>Chronic</i>   |         |  |
| Algae  | NOEC    | Green algae (Chlamydomonas variabilis) 0.41 mg/l, 21 days              |
| <b>STYRENE MONOMER (CAS 100-42-5)</b>                              |         |  |
| <b>Aquatic</b>   |         |  |
| Crustacea  | EC50    | Water flea (Daphnia magna) 3.3 - 7.4 mg/l, 48 hours                    |
| Fish   | LC50    | Sheepshead minnow (Cyprinodon variegatus) 5.1 - 16 mg/l, 96 hours      |
| <b>TITANIUM DIOXIDE (CAS 13463-67-7)</b>                           |         |  |
| <b>Aquatic</b>   |         |  |
| Crustacea  | EC50    | Water flea (Daphnia magna) > 1000 mg/l, 48 hours                       |
| Fish   | LC50    | Mummichog (Fundulus heteroclitus) > 1000 mg/l, 96 hours                |

\* Estimates for product may be based on additional component data not shown.

**Persistence and degradability** No data is available on the degradability of this product.

**Bioaccumulative potential**

**Partition coefficient n-octanol / water (log Kow)**

|  |             |
|--|-------------|
| ETHYLBENZENE                               | 3.15        |
| NAPHTHA (PETROLEUM), HYDROSULFURIZED HEAVY | 3.16 - 7.15 |
| PCBTF, P-Chlorobenzotrifluoride            | 3.7         |
| STYRENE MONOMER                            | 2.95        |

**Mobility in soil** No data available.

**Other adverse effects** No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

**13. Disposal considerations**

|  |  |
|--|--|
| <b>Disposal instructions</b>                 | Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.                         |
| <b>Local disposal regulations</b>            | Dispose in accordance with all applicable regulations.   |
| <b>Hazardous waste code</b>                  | The waste code should be assigned in discussion between the user, the producer and the waste disposal company.   |
| <b>Waste from residues / unused products</b> | Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions). |
| <b>Contaminated packaging</b>                | Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.       |

**14. Transport information**

|                                |   |
|--------------------------------|---|
| <b>DOT</b>                     |   |
| <b>UN number</b>               | UN1263  |
| <b>UN proper shipping name</b> | Paint including paint, lacquer, enamel, stain, shellac solutions, varnish, polish, liquid filler, and liquid lacquer base |



|                                     |   |
|-------------------------------------|---|
| <b>Transport hazard class(es)</b>   |   |
| Class                               | 3   |
| Subsidiary risk                     | -   |
| Label(s)                            | 3   |
| <b>Packing group</b>                | III   |
| <b>Special precautions for user</b> | Read safety instructions, SDS and emergency procedures before handling. |
| <b>Special provisions</b>           | B1, B52, IB3, T2, TP1, TP29   |
| <b>Packaging exceptions</b>         | 150   |
| <b>Packaging non bulk</b>           | 173   |
| <b>Packaging bulk</b>               | 242   |

**IATA**

|                                     |  |
|-------------------------------------|--|
| <b>UN number</b>                    | UN1263   |
| <b>UN proper shipping name</b>      | Paint (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) |
| <b>Transport hazard class(es)</b>   |  |
| Class                               | 3  |
| Subsidiary risk                     | -  |
| <b>Packing group</b>                | III  |
| <b>Environmental hazards</b>        | Yes  |
| <b>ERG Code</b>                     | 3L   |
| <b>Special precautions for user</b> | Read safety instructions, SDS and emergency procedures before handling.  |
| <b>Other information</b>            |  |
| <b>Passenger and cargo aircraft</b> | Allowed.   |
| <b>Cargo aircraft only</b>          | Allowed.   |

**IMDG**

|   |  |
|---|--|
| <b>UN number</b>  | UN1263   |
| <b>UN proper shipping name</b>  | PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound) |
| <b>Transport hazard class(es)</b>   |  |
| Class   | 3  |
| Subsidiary risk   | -  |
| <b>Packing group</b>  | III  |
| <b>Environmental hazards</b>  |  |
| <b>Marine pollutant</b>   | Yes  |
| <b>EmS</b>  | F-E, S-E   |
| <b>Special precautions for user</b>   | Read safety instructions, SDS and emergency procedures before handling.  |
| <b>Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code</b> | Not established.   |

**DOT**



IATA; IMDG



Marine pollutant



General information

IMDG Regulated Marine Pollutant.

## 15. Regulatory information

### US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

#### TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

PCBTf, P-Chlorobenzotrifluoride (CAS 98-56-6) 1.0 % One-Time Export Notification only.

#### CERCLA Hazardous Substance List (40 CFR 302.4)

ETHYLBENZENE (CAS 100-41-4) Listed.

STYRENE MONOMER (CAS 100-42-5) Listed.

#### SARA 304 Emergency release notification

Not regulated.

#### OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

### Superfund Amendments and Reauthorization Act of 1986 (SARA)

#### Hazard categories

Immediate Hazard - Yes  
Delayed Hazard - Yes  
Fire Hazard - Yes  
Pressure Hazard - No  
Reactivity Hazard - No

#### SARA 302 Extremely hazardous substance

Not listed.

**SARA 311/312 Hazardous chemical** No

#### SARA 313 (TRI reporting)

| Chemical name   | CAS number | % by wt. |
|-----------------|------------|----------|
| ETHYLBENZENE    | 100-41-4   | < 1      |
| STYRENE MONOMER | 100-42-5   | < 0.2    |

### Other federal regulations

#### Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

ETHYLBENZENE (CAS 100-41-4)

STYRENE MONOMER (CAS 100-42-5)

#### Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

**Safe Drinking Water Act (SDWA)** Not regulated.

## US state regulations

### US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed.

### US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

BIS(1,2,2,6,6-PENTAMETHYL-4-PIPERIDINYL)SEBACATE (CAS 41556-26-7)  
ETHYLBENZENE (CAS 100-41-4)  
NAPHTHA (PETROLEUM), HYDROSULFURIZED HEAVY (CAS 64742-82-1)  
STYRENE MONOMER (CAS 100-42-5)  
TITANIUM DIOXIDE (CAS 13463-67-7)

### US. Massachusetts RTK - Substance List

CALCIUM CARBONATE, LIMESTONE (CAS 1317-65-3)  
ETHYLBENZENE (CAS 100-41-4)  
SILICA (CAS 7631-86-9)  
STYRENE MONOMER (CAS 100-42-5)  
TITANIUM DIOXIDE (CAS 13463-67-7)

### US. New Jersey Worker and Community Right-to-Know Act

CALCIUM CARBONATE, LIMESTONE (CAS 1317-65-3)  
ETHYLBENZENE (CAS 100-41-4)  
PCBTf, P-Chlorobenzotrifluoride (CAS 98-56-6)  
SILICA (CAS 7631-86-9)  
STYRENE MONOMER (CAS 100-42-5)  
TITANIUM DIOXIDE (CAS 13463-67-7)

### US. Pennsylvania Worker and Community Right-to-Know Law

CALCIUM CARBONATE, LIMESTONE (CAS 1317-65-3)  
ETHYLBENZENE (CAS 100-41-4)  
SILICA (CAS 7631-86-9)  
STYRENE MONOMER (CAS 100-42-5)  
TITANIUM DIOXIDE (CAS 13463-67-7)

### US. Rhode Island RTK

ETHYLBENZENE (CAS 100-41-4)  
STYRENE MONOMER (CAS 100-42-5)

### US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

#### US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

|  |                           |
|--|---------------------------|
| BENZENE (CAS 71-43-2)                      | Listed: February 27, 1987 |
| CRYSTALLINE SILICA QUARTZ (CAS 14808-60-7) | Listed: October 1, 1988   |
| ETHANOL (CAS 64-17-5)                      | Listed: April 29, 2011    |
|  | Listed: July 1, 1988      |
| ETHYLBENZENE (CAS 100-41-4)                | Listed: June 11, 2004     |
| NAPHTHALENE (CAS 91-20-3)                  | Listed: April 19, 2002    |
| TITANIUM DIOXIDE (CAS 13463-67-7)          | Listed: September 2, 2011 |

#### US - California Proposition 65 - CRT: Listed date/Developmental toxin

|                        |                           |
|------------------------|---------------------------|
| BENZENE (CAS 71-43-2)  | Listed: December 26, 1997 |
| ETHANOL (CAS 64-17-5)  | Listed: October 1, 1987   |
| METHANOL (CAS 67-56-1) | Listed: March 16, 2012    |
| TOLUENE (CAS 108-88-3) | Listed: January 1, 1991   |

#### US - California Proposition 65 - CRT: Listed date/Female reproductive toxin

|                        |                        |
|------------------------|------------------------|
| TOLUENE (CAS 108-88-3) | Listed: August 7, 2009 |
|------------------------|------------------------|

#### US - California Proposition 65 - CRT: Listed date/Male reproductive toxin

|                       |                           |
|-----------------------|---------------------------|
| BENZENE (CAS 71-43-2) | Listed: December 26, 1997 |
|-----------------------|---------------------------|

## International Inventories

| Country(s) or region        | Inventory name                                | On inventory (yes/no)* |
|-----------------------------|---|------------------------|
| United States & Puerto Rico | Toxic Substances Control Act (TSCA) Inventory | Yes                    |

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

## 16. Other information, including date of preparation or last revision

Issue date 01-27-2016

Material name: DECADE SELF-PRIMING URETHANE - WHITE/WHITE BASE

DX-85844W Version #: 01 Issue date: 01-27-2016

SDS US

11 / 12

**Version #**

01

**HMIS® ratings**

Health: 2\*  
Flammability: 3  
Physical hazard: 0

**NFPA ratings**

Health: 2  
Flammability: 3  
Instability: 0

**NFPA ratings**



**Disclaimer**

The information contained herein is based on data supplied to us from sources believed to be reliable at the date of issue. Nothing herein shall be deemed to create any warranty of any kind, express or implied, concerning the accuracy or completeness of the information provided or the results to be obtained from the use thereof. It is offered for your consideration, investigation and verification. Buyer assumes all risk of use, storage, transportation, handling and disposal of the product in compliance with applicable federal, state and local laws and regulations. This information relates to the material designated and may not be valid for such material used in combination with any other materials nor in any process.