

## 1. Identification

<b>Product identifier</b>	<b>ENGARD 400 ENVIRONMENTAL EPOXY - WHITE BASE</b>	
<b>Other means of identification</b>		
<b>Product code</b>	400FD844W	
<b>Recommended use</b>	Industrial applications.	
<b>Recommended restrictions</b>	Professional use only	
<b>Manufacturer/Importer/Supplier/Distributor information</b>		
<b>Manufacturer</b>		
<b>Company name</b>	Ellis Paint Company	
<b>Address</b>	3150 E. Pico Blvd. Los Angeles, CA 90023-3683 United States	
<b>Telephone</b>	Customer Service	(800) 672-4900
<b>Website</b>	www.ellispaint.com	
<b>E-mail</b>	info@ellispaint.com	
<b>Emergency phone number</b>	CHEMTREC	(800) 424-9300

## 2. Hazard(s) identification

<b>Physical hazards</b>	Flammable liquids	Category 2
<b>Health hazards</b>	Serious eye damage/eye irritation	Category 2A
	Carcinogenicity	Category 1A
	Reproductive toxicity (the unborn child)	Category 2
	Specific target organ toxicity, repeated exposure	Category 1
<b>Environmental hazards</b>	Not classified.	
<b>OSHA defined hazards</b>	Not classified.	

### Label elements



**Signal word** Danger

**Hazard statement** Highly flammable liquid and vapor. Causes serious eye irritation. May cause cancer. Suspected of damaging the unborn child. Causes damage to organs through prolonged or repeated exposure.

### Precautionary statement

#### Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe mist or vapor. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Wear eye protection/face protection. Wear protective gloves/protective clothing/eye protection/face protection.

#### Response

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed or concerned: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. In case of fire: Use appropriate media to extinguish.

#### Storage

Store in a well-ventilated place. Keep cool. Store locked up.

#### Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

### Hazard(s) not otherwise classified (HNOC)

Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion.

### 3. Composition/information on ingredients

#### Mixtures

Chemical name	Common name and synonyms	CAS number	%
CRYSTALLINE SILICA QUARTZ		14808-60-7	20 - < 30
TITANIUM DIOXIDE		13463-67-7	10 - < 20
METHYL ETHYL KETONE(MEK)		78-93-3	5 - < 10
DIMETHYLBENZENE (MIXED ISOMERS)		1330-20-7	1 - < 3
METHYL ISOBUTYL KETONE(MIBK)		108-10-1	1 - < 3
SILICA		7631-86-9	1 - < 3
ETHYLBENZENE		100-41-4	< 1
CRYSTALLINE SILICA		14464-46-1	< 0.3

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

### 4. First-aid measures

<b>Inhalation</b>	Move to fresh air. Call a physician if symptoms develop or persist.
<b>Skin contact</b>	Take off immediately all contaminated clothing. Rinse skin with water/shower. Get medical attention if irritation develops and persists.
<b>Eye contact</b>	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
<b>Ingestion</b>	Rinse mouth. Get medical attention if symptoms occur.
<b>Most important symptoms/effects, acute and delayed</b>	Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Coughing. Prolonged exposure may cause chronic effects.
<b>Indication of immediate medical attention and special treatment needed</b>	Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.
<b>General information</b>	Take off all contaminated clothing immediately. IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

### 5. Fire-fighting measures

<b>Suitable extinguishing media</b>	Water fog. Foam. Carbon dioxide (CO2). Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.
<b>Unsuitable extinguishing media</b>	Do not use water jet as an extinguisher, as this will spread the fire.
<b>Specific hazards arising from the chemical</b>	Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. This product is a poor conductor of electricity and can become electrostatically charged. If sufficient charge is accumulated, ignition of flammable mixtures can occur. To reduce potential for static discharge, use proper bonding and grounding procedures. This liquid may accumulate static electricity when filling properly grounded containers. Static electricity accumulation may be significantly increased by the presence of small quantities of water or other contaminants. Material will float and may ignite on surface of water. During fire, gases hazardous to health may be formed.
<b>Special protective equipment and precautions for firefighters</b>	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
<b>Fire fighting equipment/instructions</b>	In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.
<b>Specific methods</b>	Use standard firefighting procedures and consider the hazards of other involved materials.
<b>General fire hazards</b>	Highly flammable liquid and vapor.

## 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Use appropriate containment to avoid environmental contamination. Transfer by mechanical means such as vacuum truck to a salvage tank or other suitable container for recovery or safe disposal. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

### Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Take precautionary measures against static discharge. Use only non-sparking tools. Keep combustibles (wood, paper, oil, etc.) away from spilled material.

**Large Spills:** Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

**Small Spills:** Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

### Environmental precautions

Avoid discharge into drains, water courses or onto the ground. Use appropriate containment to avoid environmental contamination.

## 7. Handling and storage

### Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Explosion-proof general and local exhaust ventilation. Minimize fire risks from flammable and combustible materials (including combustible dust and static accumulating liquids) or dangerous reactions with incompatible materials. Handling operations that can promote accumulation of static charges include but are not limited to: mixing, filtering, pumping at high flow rates, splash filling, creating mists or sprays, tank and container filling, tank cleaning, sampling, gauging, switch loading, vacuum truck operations. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Do not breathe mist or vapor. Avoid contact with eyes. Avoid prolonged exposure. When using, do not eat, drink or smoke. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.

For additional information on equipment bonding and grounding, refer to the Canadian Electrical Code in Canada, (CSA C22.1), or the American Petroleum Institute (API) Recommended Practice 2003, "Protection Against Ignitions Arising out of Static, Lightning, and Stray Currents" or National Fire Protection Association (NFPA) 77, "Recommended Practice on Static Electricity" or National Fire Protection Association (NFPA) 70, "National Electrical Code".

### Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Eliminate sources of ignition. Avoid spark promoters. Ground/bond container and equipment. These alone may be insufficient to remove static electricity. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

## 8. Exposure controls/personal protection

### Occupational exposure limits

#### US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
DIMETHYLBENZENE (MIXED ISOMERS) (CAS 1330-20-7)	PEL	435 mg/m <sup>3</sup>	
ETHYLBENZENE (CAS 100-41-4)	PEL	100 ppm 435 mg/m <sup>3</sup>	

**US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)**

Components	Type	Value	Form
METHYL ETHYL KETONE(MEK) (CAS 78-93-3)	PEL	100 ppm 590 mg/m3	
METHYL ISOBUTYL KETONE(MIBK) (CAS 108-10-1)	PEL	200 ppm 410 mg/m3	
TITANIUM DIOXIDE (CAS 13463-67-7)	PEL	100 ppm 15 mg/m3	Total dust.

**US. OSHA Table Z-3 (29 CFR 1910.1000)**

Components	Type	Value	Form
CRYSTALLINE SILICA (CAS 14464-46-1)	TWA	0.15 mg/m3	Total dust.
CRYSTALLINE SILICA QUARTZ (CAS 14808-60-7)	TWA	0.05 mg/m3	Respirable.
		1.2 mppcf	Respirable.
		0.3 mg/m3	Total dust.
SILICA (CAS 7631-86-9)	TWA	0.1 mg/m3	Respirable.
		2.4 mppcf	Respirable.
		0.8 mg/m3 20 mppcf	

**US. ACGIH Threshold Limit Values**

Components	Type	Value	Form
CRYSTALLINE SILICA (CAS 14464-46-1)	TWA	0.025 mg/m3	Respirable fraction.
CRYSTALLINE SILICA QUARTZ (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.
DIMETHYLBENZENE (MIXED ISOMERS) (CAS 1330-20-7)	STEL	150 ppm	
ETHYLBENZENE (CAS 100-41-4)	TWA	100 ppm	
	TWA	20 ppm	
METHYL ETHYL KETONE(MEK) (CAS 78-93-3)	STEL	300 ppm	
METHYL ISOBUTYL KETONE(MIBK) (CAS 108-10-1)	TWA	200 ppm	
	STEL	75 ppm	
TITANIUM DIOXIDE (CAS 13463-67-7)	TWA	20 ppm	
	TWA	10 mg/m3	

**US. NIOSH: Pocket Guide to Chemical Hazards**

Components	Type	Value	Form
CRYSTALLINE SILICA (CAS 14464-46-1)	TWA	3 fibers/cm3	Fiber.
		3 fibers/cm3	Dust.
		5 mg/m3	Fiber, total
		5 mg/m3	fibers, total dust
CRYSTALLINE SILICA QUARTZ (CAS 14808-60-7)	TWA	0.05 mg/m3	Respirable dust.
ETHYLBENZENE (CAS 100-41-4)	STEL	545 mg/m3	
		125 ppm	

**US. NIOSH: Pocket Guide to Chemical Hazards**

Components	Type	Value	Form
METHYL ETHYL KETONE(MEK) (CAS 78-93-3)	TWA	435 mg/m3	
		100 ppm	
	STEL	885 mg/m3	
METHYL ISOBUTYL KETONE(MIBK) (CAS 108-10-1)	TWA	300 ppm	
		590 mg/m3	
	STEL	200 ppm 300 mg/m3	
SILICA (CAS 7631-86-9)	TWA	75 ppm	
		205 mg/m3	
	TWA	50 ppm 6 mg/m3	

**Biological limit values**

**ACGIH Biological Exposure Indices**

Components	Value	Determinant	Specimen	Sampling Time
DIMETHYLBENZENE (MIXED ISOMERS) (CAS 1330-20-7)	1.5 g/g	Methylhippuric acids	Creatinine in urine	*
ETHYLBENZENE (CAS 100-41-4)	0.15 g/g	Sum of mandelic acid and phenylglyoxylic acid	Creatinine in urine	*
METHYL ETHYL KETONE(MEK) (CAS 78-93-3)	2 mg/l	MEK	Urine	*
METHYL ISOBUTYL KETONE(MIBK) (CAS 108-10-1)	1 mg/l	Methyl isobutyl ketone	Urine	*

\* - For sampling details, please see the source document.

**Appropriate engineering controls**

Explosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station. Eye wash fountain and emergency showers are recommended.

**Individual protection measures, such as personal protective equipment**

**Eye/face protection**

Chemical respirator with organic vapor cartridge and full facepiece.

**Skin protection**

**Hand protection**

Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier.

**Other**

Wear suitable protective clothing. Use of an impervious apron is recommended.

**Respiratory protection**

Chemical respirator with organic vapor cartridge and full facepiece.

**Thermal hazards**

Wear appropriate thermal protective clothing, when necessary.

**General hygiene considerations**

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

**9. Physical and chemical properties**

**Appearance**

<b>Physical state</b>	Liquid.
<b>Form</b>	Liquid.
<b>Color</b>	White.
<b>Odor</b>	Mild.

<b>Odor threshold</b>	Not available.
<b>pH</b>	Not available.
<b>Melting point/freezing point</b>	3.2 °F (-16 °C) estimated
<b>Initial boiling point and boiling range</b>	399.2 °F (204 °C) estimated
<b>Flash point</b>	19.4 °F (-7.0 °C) estimated
<b>Evaporation rate</b>	Not available.
<b>Flammability (solid, gas)</b>	Not applicable.
<b>Upper/lower flammability or explosive limits</b>	
<b>Flammability limit - lower (%)</b>	Not available.
<b>Flammability limit - upper (%)</b>	Not available.
<b>Explosive limit - lower (%)</b>	Not available.
<b>Explosive limit - upper (%)</b>	Not available.
<b>Vapor pressure</b>	93.33 hPa estimated
<b>Vapor density</b>	Not available.
<b>Relative density</b>	Not available.
<b>Solubility(ies)</b>	
<b>Solubility (water)</b>	Not available.
<b>Partition coefficient (n-octanol/water)</b>	Not available.
<b>Auto-ignition temperature</b>	759.2 °F (404 °C) estimated
<b>Decomposition temperature</b>	Not available.
<b>Viscosity</b>	Not available.
<b>Other information</b>	
<b>Density</b>	12.77 lbs/gal
<b>Explosive properties</b>	Not explosive.
<b>Flammability class</b>	Flammable IB estimated
<b>Oxidizing properties</b>	Not oxidizing.
<b>Percent volatile</b>	13 % estimated
<b>Specific gravity</b>	1.53
<b>VOC</b>	1.65 lbs/gal (197.92 g/l) Coating VOC 1.65 lbs/gal (197.92 g/l) Material VOC 1.81 lbs/gal (217.08 g/l) Coating VOC as applied 1.81 lbs/gal (217.08 g/l) Material VOC as applied

## 10. Stability and reactivity

<b>Reactivity</b>	The product is stable and non-reactive under normal conditions of use, storage and transport.
<b>Chemical stability</b>	Material is stable under normal conditions.
<b>Possibility of hazardous reactions</b>	Hazardous polymerization does not occur.
<b>Conditions to avoid</b>	Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
<b>Incompatible materials</b>	Strong acids. Strong oxidizing agents. Powerful oxidizers. Halogens. Ammonia. Amines. Isocyanates. Caustics. Chlorine.
<b>Hazardous decomposition products</b>	No hazardous decomposition products are known.

## 11. Toxicological information

### Information on likely routes of exposure

<b>Inhalation</b>	May cause damage to organs through prolonged or repeated exposure by inhalation.
<b>Skin contact</b>	No adverse effects due to skin contact are expected.
<b>Eye contact</b>	Causes serious eye irritation.

**Ingestion**

Expected to be a low ingestion hazard.

**Symptoms related to the physical, chemical and toxicological characteristics**

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Coughing.

**Information on toxicological effects****Acute toxicity**

Components	Species	Test Results
DIMETHYLBENZENE (MIXED ISOMERS) (CAS 1330-20-7)		
<b>Acute</b>		
<b>Dermal</b>		
LD50	Rabbit	> 43 g/kg
<b>Inhalation</b>		
LC50	Mouse	3907 mg/l, 6 Hours
	Rat	6350 mg/l, 4 Hours
<b>Oral</b>		
LD50	Mouse	1590 mg/kg
	Rat	3523 - 8600 mg/kg
ETHYLBENZENE (CAS 100-41-4)		
<b>Acute</b>		
<b>Dermal</b>		
LD50	Rabbit	17800 mg/kg
<b>Oral</b>		
LD50	Rat	3500 mg/kg
METHYL ETHYL KETONE(MEK) (CAS 78-93-3)		
<b>Acute</b>		
<b>Dermal</b>		
LD50	Rabbit	> 8000 mg/kg
<b>Inhalation</b>		
LC50	Mouse	11000 ppm, 45 Minutes
	Rat	11700 ppm, 4 Hours
<b>Oral</b>		
LD50	Mouse	670 mg/kg
	Rat	2300 - 3500 mg/kg
METHYL ISOBUTYL KETONE(MIBK) (CAS 108-10-1)		
<b>Acute</b>		
<b>Dermal</b>		
LD50	Rabbit	> 16000 mg/kg
<b>Inhalation</b>		
LC50	Rat	8.2 mg/l, 4 Hours
<b>Oral</b>		
LD50	Rat	2080 mg/kg
SILICA (CAS 7631-86-9)		
<b>Acute</b>		
<b>Oral</b>		
LD50	Mouse	> 15000 mg/kg
	Rat	> 22500 mg/kg

\* Estimates for product may be based on additional component data not shown.

**Skin corrosion/irritation**  
**Serious eye damage/eye irritation**

Prolonged skin contact may cause temporary irritation.

Causes serious eye irritation.

## Respiratory or skin sensitization

**Respiratory sensitization** Not a respiratory sensitizer.

**Skin sensitization** This product is not expected to cause skin sensitization.

**Germ cell mutagenicity** No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

**Carcinogenicity** May cause cancer.

### IARC Monographs. Overall Evaluation of Carcinogenicity

CRYSTALLINE SILICA (CAS 14464-46-1)	1 Carcinogenic to humans.
CRYSTALLINE SILICA QUARTZ (CAS 14808-60-7)	1 Carcinogenic to humans.
DIMETHYLBENZENE (MIXED ISOMERS) (CAS 1330-20-7)	3 Not classifiable as to carcinogenicity to humans.
ETHYLBENZENE (CAS 100-41-4)	2B Possibly carcinogenic to humans.
METHYL ISOBUTYL KETONE(MIBK) (CAS 108-10-1)	2B Possibly carcinogenic to humans.
SILICA (CAS 7631-86-9)	3 Not classifiable as to carcinogenicity to humans.
TITANIUM DIOXIDE (CAS 13463-67-7)	2B Possibly carcinogenic to humans.

### OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

### US. National Toxicology Program (NTP) Report on Carcinogens

CRYSTALLINE SILICA (CAS 14464-46-1)	Known To Be Human Carcinogen. Reasonably Anticipated to be a Human Carcinogen.
CRYSTALLINE SILICA QUARTZ (CAS 14808-60-7)	Known To Be Human Carcinogen.

**Reproductive toxicity** Components in this product have been shown to cause birth defects and reproductive disorders in laboratory animals. Suspected of damaging the unborn child.

**Specific target organ toxicity - single exposure** Not classified.

**Specific target organ toxicity - repeated exposure** Causes damage to organs through prolonged or repeated exposure.

**Aspiration hazard** Not an aspiration hazard.

**Chronic effects** Causes damage to organs through prolonged or repeated exposure. Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

## 12. Ecological information

**Ecotoxicity** The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components	Species	Test Results
DIMETHYLBENZENE (MIXED ISOMERS) (CAS 1330-20-7)		
<b>Aquatic</b>		
Fish LC50	Bluegill ( <i>Lepomis macrochirus</i> )	7.711 - 9.591 mg/l, 96 hours
ETHYLBENZENE (CAS 100-41-4)		
<b>Aquatic</b>		
Crustacea EC50	Water flea ( <i>Daphnia magna</i> )	1.37 - 4.4 mg/l, 48 hours
Fish LC50	Fathead minnow ( <i>Pimephales promelas</i> )	7.5 - 11 mg/l, 96 hours
METHYL ETHYL KETONE(MEK) (CAS 78-93-3)		
<b>Aquatic</b>		
Crustacea EC50	Water flea ( <i>Daphnia magna</i> )	4025 - 6440 mg/l, 48 hours
Fish LC50	Sheepshead minnow ( <i>Cyprinodon variegatus</i> )	> 400 mg/l, 96 hours
METHYL ISOBUTYL KETONE(MIBK) (CAS 108-10-1)		
<b>Aquatic</b>		
Fish LC50	Fathead minnow ( <i>Pimephales promelas</i> )	492 - 593 mg/l, 96 hours
TITANIUM DIOXIDE (CAS 13463-67-7)		
<b>Aquatic</b>		
Crustacea EC50	Water flea ( <i>Daphnia magna</i> )	> 1000 mg/l, 48 hours



Components	Species	Test Results
Fish	LC50	Mummichog (Fundulus heteroclitus)
		> 1000 mg/l, 96 hours

\* Estimates for product may be based on additional component data not shown.

**Persistence and degradability** No data is available on the degradability of this product.

**Bioaccumulative potential**

**Partition coefficient n-octanol / water (log Kow)**

DIMETHYLBENZENE (MIXED ISOMERS)	3.12 - 3.2
ETHYLBENZENE	3.15
METHYL ETHYL KETONE(MEK)	0.29
METHYL ISOBUTYL KETONE(MIBK)	1.38

**Mobility in soil** No data available.

**Other adverse effects** No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

### 13. Disposal considerations

**Disposal instructions** Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.

**Local disposal regulations** Dispose in accordance with all applicable regulations.

**Hazardous waste code** The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

**Waste from residues / unused products** Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

**Contaminated packaging** Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

### 14. Transport information

**DOT**

**UN number** UN1263

**UN proper shipping name** Paint including paint, lacquer, enamel, stain, shellac solutions, varnish, polish, liquid filler, and liquid lacquer base

**Transport hazard class(es)**

**Class** 3

**Subsidiary risk** -

**Label(s)** 3

**Packing group** II

**Special precautions for user** Read safety instructions, SDS and emergency procedures before handling.

**Special provisions** 149, B52, IB2, T4, TP1, TP8, TP28

**Packaging exceptions** 150

**Packaging non bulk** 173

**Packaging bulk** 242

**IATA**

**UN number** UN1263

**UN proper shipping name** Paint (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base)

**Transport hazard class(es)**

**Class** 3

**Subsidiary risk** -

**Packing group** II

**Environmental hazards** No.

**ERG Code** 3L

**Special precautions for user** Read safety instructions, SDS and emergency procedures before handling.

**Other information**

**Passenger and cargo aircraft** Allowed.

**Cargo aircraft only** Allowed.

**IMDG**

**UN number** UN1263

**UN proper shipping name** PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound)

**Transport hazard class(es)**

**Class** 3

**Subsidiary risk** -

**Packing group** II

**Environmental hazards**

**Marine pollutant** No.

**EmS** F-E, S-E

**Special precautions for user** Read safety instructions, SDS and emergency procedures before handling.

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code** Not established.

DOT



IATA; IMDG



## 15. Regulatory information

**US federal regulations** This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

### TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

### CERCLA Hazardous Substance List (40 CFR 302.4)

DIMETHYLBENZENE (MIXED ISOMERS) (CAS 1330-20-7)	Listed.
ETHYLBENZENE (CAS 100-41-4)	Listed.
METHYL ETHYL KETONE (MEK) (CAS 78-93-3)	Listed.
METHYL ISOBUTYL KETONE (MIBK) (CAS 108-10-1)	Listed.

### SARA 304 Emergency release notification

Not regulated.

### OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

### Superfund Amendments and Reauthorization Act of 1986 (SARA)

**Hazard categories**

Immediate Hazard - Yes  
 Delayed Hazard - Yes  
 Fire Hazard - Yes  
 Pressure Hazard - No  
 Reactivity Hazard - No

### SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical No

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
DIMETHYLBENZENE (MIXED ISOMERS)	1330-20-7	1 - < 3
METHYL ISOBUTYL KETONE(MIBK)	108-10-1	1 - < 3
ETHYLBENZENE	100-41-4	< 1

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

DIMETHYLBENZENE (MIXED ISOMERS) (CAS 1330-20-7)  
ETHYLBENZENE (CAS 100-41-4)  
METHYL ISOBUTYL KETONE(MIBK) (CAS 108-10-1)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Not regulated.

Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number

METHYL ETHYL KETONE(MEK) (CAS 78-93-3) 6714  
METHYL ISOBUTYL KETONE(MIBK) (CAS 108-10-1) 6715

Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

METHYL ETHYL KETONE(MEK) (CAS 78-93-3) 35 %WV  
METHYL ISOBUTYL KETONE(MIBK) (CAS 108-10-1) 35 %WV

DEA Exempt Chemical Mixtures Code Number

METHYL ETHYL KETONE(MEK) (CAS 78-93-3) 6714  
METHYL ISOBUTYL KETONE(MIBK) (CAS 108-10-1) 6715

US state regulations

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed.

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

CRYSTALLINE SILICA (CAS 14464-46-1)  
CRYSTALLINE SILICA QUARTZ (CAS 14808-60-7)  
DIMETHYLBENZENE (MIXED ISOMERS) (CAS 1330-20-7)  
ETHYLBENZENE (CAS 100-41-4)  
METHYL ETHYL KETONE(MEK) (CAS 78-93-3)  
METHYL ISOBUTYL KETONE(MIBK) (CAS 108-10-1)  
TITANIUM DIOXIDE (CAS 13463-67-7)

US. Massachusetts RTK - Substance List

CRYSTALLINE SILICA (CAS 14464-46-1)  
CRYSTALLINE SILICA QUARTZ (CAS 14808-60-7)  
DIMETHYLBENZENE (MIXED ISOMERS) (CAS 1330-20-7)  
ETHYLBENZENE (CAS 100-41-4)  
METHYL ETHYL KETONE(MEK) (CAS 78-93-3)  
METHYL ISOBUTYL KETONE(MIBK) (CAS 108-10-1)  
SILICA (CAS 7631-86-9)  
TITANIUM DIOXIDE (CAS 13463-67-7)

US. New Jersey Worker and Community Right-to-Know Act

CRYSTALLINE SILICA (CAS 14464-46-1)  
CRYSTALLINE SILICA QUARTZ (CAS 14808-60-7)  
DIMETHYLBENZENE (MIXED ISOMERS) (CAS 1330-20-7)  
ETHYLBENZENE (CAS 100-41-4)  
METHYL ETHYL KETONE(MEK) (CAS 78-93-3)  
METHYL ISOBUTYL KETONE(MIBK) (CAS 108-10-1)  
SILICA (CAS 7631-86-9)  
TITANIUM DIOXIDE (CAS 13463-67-7)

## US. Pennsylvania Worker and Community Right-to-Know Law

CRYSTALLINE SILICA (CAS 14464-46-1)  
CRYSTALLINE SILICA QUARTZ (CAS 14808-60-7)  
DIMETHYLBENZENE (MIXED ISOMERS) (CAS 1330-20-7)  
ETHYLBENZENE (CAS 100-41-4)  
METHYL ETHYL KETONE(MEK) (CAS 78-93-3)  
METHYL ISOBUTYL KETONE(MIBK) (CAS 108-10-1)  
SILICA (CAS 7631-86-9)  
TITANIUM DIOXIDE (CAS 13463-67-7)

## US. Rhode Island RTK

DIMETHYLBENZENE (MIXED ISOMERS) (CAS 1330-20-7)  
ETHYLBENZENE (CAS 100-41-4)  
METHYL ETHYL KETONE(MEK) (CAS 78-93-3)  
METHYL ISOBUTYL KETONE(MIBK) (CAS 108-10-1)

## US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

### US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

CRYSTALLINE SILICA QUARTZ (CAS 14808-60-7)	Listed: October 1, 1988
ETHYLBENZENE (CAS 100-41-4)	Listed: June 11, 2004
METHYL ISOBUTYL KETONE(MIBK) (CAS 108-10-1)	Listed: November 4, 2011
TITANIUM DIOXIDE (CAS 13463-67-7)	Listed: September 2, 2011

### US - California Proposition 65 - CRT: Listed date/Developmental toxin

METHYL ISOBUTYL KETONE(MIBK) (CAS 108-10-1)	Listed: March 28, 2014
TOLUENE (CAS 108-88-3)	Listed: January 1, 1991

### US - California Proposition 65 - CRT: Listed date/Female reproductive toxin

TOLUENE (CAS 108-88-3)	Listed: August 7, 2009
------------------------	------------------------

## International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

## 16. Other information, including date of preparation or last revision

Issue date	12-11-2015
Version #	01
HMIS® ratings	Health: 2* Flammability: 3 Physical hazard: 0
NFPA ratings	Health: 2 Flammability: 3 Instability: 0

## NFPA ratings



## Disclaimer

The information contained herein is based on data supplied to us from sources believed to be reliable at the date of issue. Nothing herein shall be deemed to create any warranty of any kind, express or implied, concerning the accuracy or completeness of the information provided or the results to be obtained from the use thereof. It is offered for your consideration, investigation and verification. Buyer assumes all risk of use, storage, transportation, handling and disposal of the product in compliance with applicable federal, state and local laws and regulations. This information relates to the material designated and may not be valid for such material used in combination with any other materials nor in any process.