

1. Identification

Product identifier WATERBORNE INDUSTRIAL ENAMEL - CLEAR SATIN

Other means of identification

Product code 1455

Recommended use Industrial applications.

Recommended restrictions Professional use only

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name Ellis Paint Company
Address 3150 E. Pico Blvd.
 Los Angeles, CA 90023-3683
 United States
Telephone Customer Service (800) 672-4900
Website www.ellispaint.com
E-mail info@ellispaint.com
Emergency phone number CHEMTREC (800) 424-9300

2. Hazard(s) identification

Physical hazards Flammable liquids Category 4

Health hazards Sensitization, skin Category 1

Reproductive toxicity Category 1

Environmental hazards Not classified.

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Combustible liquid. May cause an allergic skin reaction. May damage fertility or the unborn child.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from flames and hot surfaces-No smoking. Avoid breathing mist or vapor. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection.

Response If on skin: Wash with plenty of water. If exposed or concerned: Get medical advice/attention. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse. In case of fire: Use appropriate media to extinguish.

Storage Store in a well-ventilated place. Keep cool. Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC) None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
2-BUTOXY ETHANOL		111-76-2	5 - < 10
TALC		14807-96-6	5 - < 10

Chemical name	Common name and synonyms	CAS number	%
BUTYL BENZYL PHTHALATE		85-68-7	1 - < 3
DIETHYLENE GLYCOL MONOBUTYL ETHER		112-34-5	1 - < 3
BIS(1,2,2,6,6-PENTAMETHYL-4-PERIDINYL)SEBACATE		41556-26-7	< 1
AMMONIA		7664-41-7	< 0.2

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation	Move to fresh air. Call a physician if symptoms develop or persist.
Skin contact	Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema or other skin disorders: Seek medical attention and take along these instructions.
Eye contact	Rinse with water. Get medical attention if irritation develops and persists.
Ingestion	Rinse mouth. Get medical attention if symptoms occur.
Most important symptoms/effects, acute and delayed	Direct contact with eyes may cause temporary irritation. May cause an allergic skin reaction. Dermatitis. Rash.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General information	IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media	Water fog. Foam. Dry chemical powder. Carbon dioxide (CO ₂).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	The product is combustible, and heating may generate vapors which may form explosive vapor/air mixtures. During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	Combustible liquid.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water. Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from open flames, hot surfaces and sources of ignition. When using do not smoke. Provide adequate ventilation. Do not get in eyes, on skin, or on clothing. Avoid breathing mist or vapor. Avoid prolonged exposure. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat, sparks and open flame. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
2-BUTOXY ETHANOL (CAS 111-76-2)	PEL	240 mg/m3
AMMONIA (CAS 7664-41-7)	PEL	50 ppm
		35 mg/m3
		50 ppm

US. OSHA Table Z-3 (29 CFR 1910.1000)

Components	Type	Value	Form
TALC (CAS 14807-96-6)	TWA	0.3 mg/m3	Total dust.
		0.1 mg/m3	Respirable.
		20 mppcf	
		2.4 mppcf	Respirable.

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
2-BUTOXY ETHANOL (CAS 111-76-2)	TWA	20 ppm	
AMMONIA (CAS 7664-41-7)	STEL	35 ppm	
		25 ppm	
DIETHYLENE GLYCOL MONOBUTYL ETHER (CAS 112-34-5)	TWA	10 ppm	Inhalable fraction and vapor.
TALC (CAS 14807-96-6)	TWA	2 mg/m3	Respirable fraction.

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value	Form
2-BUTOXY ETHANOL (CAS 111-76-2)	TWA	24 mg/m3	
		5 ppm	
AMMONIA (CAS 7664-41-7)	STEL	27 mg/m3	
		35 ppm	
TALC (CAS 14807-96-6)	TWA	18 mg/m3	
		25 ppm	
		2 mg/m3	Respirable.

Biological limit values

ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
2-BUTOXY ETHANOL (CAS 111-76-2)	200 mg/g	Butoxyacetic acid (BAA), with hydrolysis	Creatinine in urine	*

* - For sampling details, please see the source document.

Exposure guidelines

US - California OELs: Skin designation

2-BUTOXY ETHANOL (CAS 111-76-2) Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies

2-BUTOXY ETHANOL (CAS 111-76-2) Skin designation applies.

US - Tennessee OELs: Skin designation

2-BUTOXY ETHANOL (CAS 111-76-2) Can be absorbed through the skin.

US NIOSH Pocket Guide to Chemical Hazards: Skin designation

2-BUTOXY ETHANOL (CAS 111-76-2) Can be absorbed through the skin.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

2-BUTOXY ETHANOL (CAS 111-76-2) Can be absorbed through the skin.

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protection

Chemical respirator with organic vapor cartridge and full facepiece.

Skin protection

Hand protection

Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier.

Other

Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Respiratory protection

Chemical respirator with organic vapor cartridge and full facepiece.

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties

Appearance

Physical state

Liquid.

Form

Liquid.

Color

Clear.

Odor

Mild.

Odor threshold

Not available.

pH

Not available.

Melting point/freezing point

32 °F (0 °C) estimated

Initial boiling point and boiling range

212 °F (100 °C) estimated

Flash point

143.1 °F (61.7 °C) estimated

Evaporation rate

Not available.

Flammability (solid, gas)

Not applicable.

Upper/lower flammability or explosive limits

Flammability limit - lower (%)

Not available.

Flammability limit - upper (%)

Not available.

Explosive limit - lower (%)

Not available.

Explosive limit - upper (%)

Not available.

Vapor pressure

20.66 hPa estimated

Vapor density

Not available.

Relative density

Not available.

Solubility(ies)

Solubility (water)

Not available.

Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Density	9.01 lbs/gal
Explosive properties	Not explosive.
Flammability class	Combustible IIIA estimated
Oxidizing properties	Not oxidizing.
Percent volatile	58 % estimated
Specific gravity	1.08
VOC	1.62 lbs/gal (194.64 g/l) Coating VOC 0.7 lbs/gal (84.25 g/l) Material VOC

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation	Prolonged inhalation may be harmful.
Skin contact	May cause an allergic skin reaction.

2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and prolonged. These effects have not been observed in humans.

Eye contact	Direct contact with eyes may cause temporary irritation.
Ingestion	Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics	May cause an allergic skin reaction. Dermatitis. Rash.
---	--

Information on toxicological effects

Acute toxicity	May cause an allergic skin reaction.
-----------------------	--------------------------------------

Components	Species	Test Results
------------	---------	--------------

2-BUTOXY ETHANOL (CAS 111-76-2)

Acute

Dermal

LD50	Rabbit	400 mg/kg
------	--------	-----------

Inhalation

LC50	Mouse	700 ppm, 7 Hours
	Rat	450 ppm, 4 Hours

Oral

LD50	Guinea pig	1.2 g/kg
	Mouse	1.2 g/kg
	Rabbit	0.32 g/kg

Components	Species	Test Results
	Rat	560 mg/kg
AMMONIA (CAS 7664-41-7)		
Acute		
Inhalation		
LC50	Cat	0.746 mg/l, 1 Hours
	Mouse	7.105 mg/l, 10 Minutes
		3.36 mg/l, 1 Hours
		3.31 mg/l, 2 Hours
	Rabbit	7.05 mg/l, 1 Hours
	Rat	4000 ppm, 1 Hours
		7.6 mg/l, 2 Hours
		5.1 mg/l, 1 Hours
Oral		
LD50	Rat	350 mg/kg
BUTYL BENZYL PHTHALATE (CAS 85-68-7)		
Acute		
Dermal		
LD50	Mouse	6700 mg/kg
	Rat	6700 mg/kg
Oral		
LD50	Rat	13500 mg/kg
DIETHYLENE GLYCOL MONOBUTYL ETHER (CAS 112-34-5)		
Acute		
Dermal		
LD50	Rabbit	2700 mg/kg
Oral		
LD50	Guinea pig	2000 mg/kg
	Mouse	2400 mg/kg
	Rabbit	2200 mg/kg
	Rat	4500 mg/kg

* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye irritation Direct contact with eyes may cause temporary irritation.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization May cause an allergic skin reaction.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

IARC Monographs. Overall Evaluation of Carcinogenicity

2-BUTOXY ETHANOL (CAS 111-76-2) 3 Not classifiable as to carcinogenicity to humans.

BUTYL BENZYL PHTHALATE (CAS 85-68-7) 3 Not classifiable as to carcinogenicity to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Reproductive toxicity May damage fertility or the unborn child.

Specific target organ toxicity - single exposure Not classified.

Specific target organ toxicity - repeated exposure Not classified.

Aspiration hazard Not an aspiration hazard.

Chronic effects May be harmful if absorbed through skin. Prolonged inhalation may be harmful.

2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and prolonged. These effects have not been observed in humans.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components	Species	Test Results
2-BUTOXY ETHANOL (CAS 111-76-2)		
Aquatic		
Fish	LC50	Inland silverside (<i>Menidia beryllina</i>) 1250 mg/l, 96 hours
AMMONIA (CAS 7664-41-7)		
Aquatic		
Fish	LC50	Chinook salmon (<i>Oncorhynchus tshawytscha</i>) 0.43 - 0.47 mg/l, 96 hours
BUTYL BENZYL PHTHALATE (CAS 85-68-7)		
Aquatic		
Crustacea	EC50	Water flea (<i>Daphnia magna</i>) > 0.96 mg/l, 48 hours
Fish	LC50	Shiner perch (<i>Cymatogaster aggregata</i>) 0.47 - 0.56 mg/l, 96 hours
DIETHYLENE GLYCOL MONOBUTYL ETHER (CAS 112-34-5)		
Aquatic		
Fish	LC50	Bluegill (<i>Lepomis macrochirus</i>) 1300 mg/l, 96 hours

* Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

2-BUTOXY ETHANOL	0.83
BUTYL BENZYL PHTHALATE	3.57 - 4.91
DIETHYLENE GLYCOL MONOBUTYL ETHER	0.56

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

Waste from residues / unused products Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not established.

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

TSCA Chemical Action Plans, Chemicals of Concern

BUTYL BENZYL PHTHALATE (CAS 85-68-7) Phthalates Action Plan

CERCLA Hazardous Substance List (40 CFR 302.4)

2-BUTOXY ETHANOL (CAS 111-76-2) Listed.
 AMMONIA (CAS 7664-41-7) Listed.
 BUTYL BENZYL PHTHALATE (CAS 85-68-7) Listed.
 DIETHYLENE GLYCOL MONOBUTYL ETHER (CAS 112-34-5) Listed.

SARA 304 Emergency release notification

AMMONIA (CAS 7664-41-7) 100 LBS

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes
 Delayed Hazard - Yes
 Fire Hazard - Yes
 Pressure Hazard - No
 Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Chemical name	CAS number	Reportable quantity	Threshold planning quantity	Threshold planning quantity, lower value	Threshold planning quantity, upper value
AMMONIA	7664-41-7	100	500 lbs		

SARA 311/312 Hazardous chemical No

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
2-BUTOXY ETHANOL	111-76-2	5 - < 10
DIETHYLENE GLYCOL MONOBUTYL ETHER	112-34-5	1 - < 3

Other federal regulations**Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

DIETHYLENE GLYCOL MONOBUTYL ETHER (CAS 112-34-5)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

AMMONIA (CAS 7664-41-7)

Safe Drinking Water Act (SDWA) Not regulated.

US state regulations**US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)**

Not listed.

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

2-BUTOXY ETHANOL (CAS 111-76-2)
 AMMONIA (CAS 7664-41-7)
 BIS(1,2,2,6,6-PENTAMETHYL-4-PIPERIDINYL)SEBACATE (CAS 41556-26-7)
 BUTYL BENZYL PHTHALATE (CAS 85-68-7)
 DIETHYLENE GLYCOL MONOBUTYL ETHER (CAS 112-34-5)

TALC (CAS 14807-96-6)

US. Massachusetts RTK - Substance List

2-BUTOXY ETHANOL (CAS 111-76-2)
AMMONIA (CAS 7664-41-7)
BUTYL BENZYL PHTHALATE (CAS 85-68-7)
TALC (CAS 14807-96-6)

US. New Jersey Worker and Community Right-to-Know Act

2-BUTOXY ETHANOL (CAS 111-76-2)
AMMONIA (CAS 7664-41-7)
BUTYL BENZYL PHTHALATE (CAS 85-68-7)
DIETHYLENE GLYCOL MONOBUTYL ETHER (CAS 112-34-5)
TALC (CAS 14807-96-6)

US. Pennsylvania Worker and Community Right-to-Know Law

2-BUTOXY ETHANOL (CAS 111-76-2)
AMMONIA (CAS 7664-41-7)
BUTYL BENZYL PHTHALATE (CAS 85-68-7)
DIETHYLENE GLYCOL MONOBUTYL ETHER (CAS 112-34-5)
TALC (CAS 14807-96-6)

US. Rhode Island RTK

2-BUTOXY ETHANOL (CAS 111-76-2)
AMMONIA (CAS 7664-41-7)
BUTYL BENZYL PHTHALATE (CAS 85-68-7)
DIETHYLENE GLYCOL MONOBUTYL ETHER (CAS 112-34-5)

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

CRYSTALLINE SILICA QUARTZ (CAS 14808-60-7) Listed: October 1, 1988

US - California Proposition 65 - CRT: Listed date/Developmental toxin

BUTYL BENZYL PHTHALATE (CAS 85-68-7) Listed: December 2, 2005

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)
A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	12-11-2015
Version #	01
HMIS® ratings	Health: 2* Flammability: 2 Physical hazard: 0
NFPA ratings	Health: 2 Flammability: 2 Instability: 0

NFPA ratings



Disclaimer

The information contained herein is based on data supplied to us from sources believed to be reliable at the date of issue. Nothing herein shall be deemed to create any warranty of any kind, express or implied, concerning the accuracy or completeness of the information provided or the results to be obtained from the use thereof. It is offered for your consideration, investigation and verification. Buyer assumes all risk of use, storage, transportation, handling and disposal of the product in compliance with applicable federal, state and local laws and regulations. This information relates to the material designated and may not be valid for such material used in combination with any other materials nor in any process.