

1. Identification

Product identifier 844-1352 CHROMA-CHEM®BURNT UMBER BU

Other means of identification

SAP Specification 000000139837

Recommended use Non-aqueous colorant

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company Chromaflo Technologies Corporation
2600 Michigan Avenue
Ashtabula, OH 44005-0816
USA

Telephone 440-997-5137

Telefax 440-992-3613

US: CHEMTREC 800-424-9300

EMERGENCY NUMBER

CANADA: CANUTEC 613-996-6666

EMERGENCY NUMBER

Product Regulatory Services 440-536-9691

2. Hazard(s) identification

Physical hazards Flammable liquids Category 3

Health hazards Acute toxicity, oral Category 4

Environmental hazards Not classified.

OSHA defined hazards Not classified.

Label elements



Signal word Warning

Hazard statement Flammable liquid and vapor. Harmful if swallowed.

Precautionary statement

Prevention

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Wear protective gloves/eye protection/face protection.

Response

If swallowed: Call a poison center/doctor if you feel unwell. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. Rinse mouth. In case of fire: Use appropriate media to extinguish.

Storage

Store in a well-ventilated place. Keep cool.

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC)

None known.

Supplemental information

91.87% of the mixture consists of component(s) of unknown acute oral toxicity. If product is in liquid or paste form, physical or health hazards listed related to dust are not considered significant. However, product may contain substances that could be potential hazards if caused to become airborne due to grinding, sanding or other abrasive processes.

3. Hazardous components

Mixtures

Chemical name	Common name and synonyms	CAS number	%
PROPYLENE GLYCOL MONOMETHYL ETHER ACETATE		108-65-6	20 - 40
Aluminum oxide		1344-28-1	2.5 - 10
manganese dioxide		1313-13-9	2.5 - 10
Silica, crystalline (quartz)		14808-60-7	1 - 2.5

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation	Move to fresh air. Call a physician if symptoms develop or persist.
Skin contact	Take off immediately all contaminated clothing. Rinse skin with water/shower. Get medical attention if irritation develops and persists.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Get medical attention if irritation develops and persists.
Ingestion	Rinse mouth. IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.
Most important symptoms/effects, acute and delayed	Direct contact with eyes may cause temporary irritation.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. In case of shortness of breath, give oxygen. Keep victim warm. Keep victim under observation. Symptoms may be delayed.
General information	Take off all contaminated clothing immediately. In the case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media	Alcohol resistant foam. Water fog. Dry chemical powder. Carbon dioxide (CO ₂).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire-fighting equipment/instructions	In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	Flammable liquid and vapor.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Take precautionary measures against static discharge. Use only non-sparking tools. Keep combustibles (wood, paper, oil, etc.) away from spilled material. Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water. Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.
Environmental precautions	Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Vapors may form explosive mixtures with air. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Do not taste or swallow. Avoid prolonged exposure. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices. When using, do not eat, drink or smoke. Wash hands thoroughly after handling.

Conditions for safe storage, including any incompatibilities

Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in original tightly closed container. Store in a cool, dry place out of direct sunlight. Store in a well-ventilated place. Refrigeration recommended. Store away from incompatible materials (see Section 10 of the SDS). Keep in an area equipped with sprinklers.

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
Aluminum oxide (CAS 1344-28-1)	PEL	5 mg/m ³	Respirable fraction.
		15 mg/m ³	Total dust.
manganese dioxide (CAS 1313-13-9)	Ceiling	5 mg/m ³	

US. OSHA Table Z-3 (29 CFR 1910.1000)

Components	Type	Value	Form
Silica, crystalline (quartz) (CAS 14808-60-7)	TWA	0.3 mg/m ³	Total dust.
		0.1 mg/m ³	Respirable.
		2.4 millions of particle	Respirable.

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
Aluminum oxide (CAS 1344-28-1)	TWA	1 mg/m ³	Respirable fraction.
manganese dioxide (CAS 1313-13-9)	TWA	0.1 mg/m ³	Inhalable fraction.
		0.02 mg/m ³	Respirable fraction.
Silica, crystalline (quartz) (CAS 14808-60-7)	TWA	0.025 mg/m ³	Respirable fraction.

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value	Form
manganese dioxide (CAS 1313-13-9)	STEL	3 mg/m ³	Fume.
	TWA	1 mg/m ³	Fume.
Silica, crystalline (quartz) (CAS 14808-60-7)	TWA	0.05 mg/m ³	Respirable dust.

US. AIHA Workplace Environmental Exposure Level (WEEL) Guides

Components	Type	Value
PROPYLENE GLYCOL MONOMETHYL ETHER ACETATE (CAS 108-65-6)	TWA	50 ppm

Biological limit values

No biological exposure limits noted for the ingredient(s).

Exposure guidelines

US - California OELs: Skin designation

PROPYLENE GLYCOL MONOMETHYL ETHER ACETATE (CAS 108-65-6) Can be absorbed through the skin.

Appropriate engineering controls

Explosion-proof general and local exhaust ventilation. Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection	
Hand protection	Wear protective gloves.
Other	Wear appropriate chemical resistant clothing.
Respiratory protection	If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Use a NIOSH/MSHA approved respirator if there is a risk of exposure to vapor/mist at levels exceeding the exposure limits.
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
General hygiene considerations	When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state	Liquid.
Form	Liquid.
Color	brownish
Odor	Sweet ether-like odor.
Odor threshold	Not available.
pH	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	Not available.
Flash point	116.0 °F (46.7 °C)
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	Not available.
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Density	32.947 lbs/gal
Flammability class	Combustible II estimated

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Acids. Chlorine.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Ingestion	Harmful if swallowed.
Inhalation	Prolonged inhalation may be harmful.
Skin contact	No adverse effects due to skin contact are expected.
Eye contact	Direct contact with eyes may cause temporary irritation.

Symptoms related to the physical, chemical and toxicological characteristics Direct contact with eyes may cause temporary irritation.

Information on toxicological effects

Acute toxicity Harmful if swallowed. Expected to be a low hazard for usual industrial or commercial handling by trained personnel.

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye irritation Direct contact with eyes may cause temporary irritation.

Respiratory or skin sensitization

Respiratory sensitization Not available.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

Carcinogenicity Risk of cancer cannot be excluded with prolonged exposure.

IARC Monographs. Overall Evaluation of Carcinogenicity

Silica, crystalline (quartz) (CAS 14808-60-7) 1 Carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens

Silica, crystalline (quartz) (CAS 14808-60-7) Known To Be Human Carcinogen.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity - single exposure Not classified.

Specific target organ toxicity - repeated exposure Not classified.

Aspiration hazard Not available.

Chronic effects Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential No data available.

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. This material and its container must be disposed of as hazardous waste. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

Waste from residues / unused products Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied.

14. Transport information

DOT

UN number	UN1263
UN proper shipping name	Paint related material
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Label(s)	3
Packing group	III
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Special provisions	B1, B52, IB3, T2, TP1, TP29
Packaging exceptions	150
Packaging non bulk	173
Packaging bulk	242

DOT BULK

BULK

UN number	UN1263
UN proper shipping name	Paint related material
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Label(s)	3
Packing group	III
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Special provisions	B1, B52, IB3, T2, TP1, TP29
Packaging exceptions	150
Packaging non bulk	173
Packaging bulk	242

IATA

UN number	UN1263
UN proper shipping name	Paint related material
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Packing group	III
Environmental hazards	No.
ERG Code	3L
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Other information	
Passenger and cargo aircraft	Allowed.
Cargo aircraft only	Allowed.

IMDG

UN number	UN1263
UN proper shipping name	PAINT RELATED MATERIAL
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Packing group	III
Environmental hazards	
Marine pollutant	No.
EmS	F-E, S-E
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not available.

DOT; DOT Bulk packaging type



IATA; IMDG



15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.
All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

manganese dioxide (CAS 1313-13-9) Listed.

SARA 304 Emergency release notification

Not regulated.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Immediate Hazard - Yes
Delayed Hazard - No
Fire Hazard - Yes
Pressure Hazard - No
Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Chemical name	CAS number	Reportable quantity	Threshold planning quantity	Threshold planning quantity, lower value	Threshold planning quantity, upper value
---------------	------------	---------------------	-----------------------------	--	--

Sulfuric Acid	7664-93-9	1000	1000 lbs		
---------------	-----------	------	----------	--	--

SARA 311/312 Hazardous chemical No

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
Aluminum oxide	1344-28-1	2.5 - 10
manganese dioxide	1313-13-9	2.5 - 10

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

manganese dioxide (CAS 1313-13-9)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA)

Not regulated.

US state regulations

US. Massachusetts RTK - Substance List

Aluminum oxide (CAS 1344-28-1)
Silica, crystalline (quartz) (CAS 14808-60-7)

US. New Jersey Worker and Community Right-to-Know Act

Aluminum oxide (CAS 1344-28-1)	500 lbs
manganese dioxide (CAS 1313-13-9)	500 lbs

US. Pennsylvania RTK - Hazardous Substances

Aluminum oxide (CAS 1344-28-1)
Silica, crystalline (quartz) (CAS 14808-60-7)

US. Rhode Island RTK

Aluminum oxide (CAS 1344-28-1)
manganese dioxide (CAS 1313-13-9)

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Silica, crystalline (quartz) (CAS 14808-60-7)	Listed: October 1, 1988
Sulfuric Acid (CAS 7664-93-9)	Listed: March 14, 2003

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 12-23-2013

Revision date 05-07-2015

Version # 02

Disclaimer The information contained herein is based on data believed to be reliable and the manufacturer disclaims any liability incurred from the use or reliance upon the same. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. This safety information is not a license to use this material as claimed by any patents of third parties. The user alone must finally determine whether a contemplated use of this material will infringe any such patents, and for obtaining any required licenses.

Revision Information Product and Company Identification: Product and Company Identification
 Hazard(s) identification: Supplemental information
 Composition / Information on Ingredients: Undisclosed Ingredient Statement
 Exposure controls/personal protection: Appropriate engineering controls
 Exposure controls/personal protection: Respiratory protection
 Physical & Chemical Properties: Multiple Properties