

MATERIAL SAFETY DATA SHEET

896-7201 CHROMA-CHEM® PHTHALO BLUE APB



Material no.		Version	2.29 / US
Specification	139542	Revision date	08/27/2011
Order Number		Print Date	04/06/2013
		Page	1 / 9

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product information

Trade name : 896-7201 CHROMA-CHEM® PHTHALO BLUE APB
Use of the Substance / : Aqueous industrial colorant
Preparation
Company : Chromaflo Technologies Corporation
2600 Michigan Avenue
Ashtabula, OH 44005-0816
USA

Telephone : 440-997-5137

Telefax : 440-992-3613

US: CHEMTREC EMERGENCY : 800-424-9300
NUMBER

CANADA: CANUTEC : 613-996-6666
EMERGENCY NUMBER

Product Regulatory Services : 440-536-9691

2. HAZARDS IDENTIFICATION

*** EMERGENCY OVERVIEW ***

Form-paste Color-blue Odor-Mild acrylic odor.

May cause eye, skin and respiratory tract irritation.
May be harmful if swallowed.

POTENTIAL HEALTH EFFECTS

Eye contact

A mild irritant according to test results on CHROMA-CHEM® base mixtures. Can cause tearing and reddening.

Skin Contact

A mild irritant according to test results on CHROMA-CHEM® base mixtures. Repeated exposure may cause drying of the skin.

Inhalation

Possibly irritating.

If misted, causes irritation of mucous membranes, nose, eyes, and throat. May cause coughing and difficulty in breathing.

Ingestion

MATERIAL SAFETY DATA SHEET**896-7201 CHROMA-CHEM® PHTHALO BLUE****APB**

Material no.		Version	2.29 / US
Specification	139542	Revision date	08/27/2011
Order Number		Print Date	04/06/2013
		Page	2 / 9

May cause gastrointestinal irritation, nausea, vomiting, and diarrhea.

Diethylene glycol monomethyl ether has been shown to cause toxic effects on the thymus and the spleen in tests on laboratory animals.

Diethylene glycol monomethyl ether has been shown to cause fetotoxicity and teratogenicity via oral route in tests on laboratory animals.

May be harmful if swallowed.

Chronic Health Hazard

The NJTSR No. 56705700001-5020P, is moderately toxic and may be harmful if swallowed, inhaled or absorbed through the skin. This material may also stimulate the central nervous system, possibly resulting in restlessness, uncoordination, tremors and convulsions.

Oral doses of Diethylene glycol monomethyl ether that were high enough to cause maternal toxicity in pregnant laboratory test animals also produced birth defects in their offspring. When applied continuously to the skin of laboratory test animals during pregnancy, this material caused slight embryofetal toxicity (delayed development) but no increase in birth defects. The relevance of this information to humans is not known. Overexposure to this material has been suggested as a cause of the following effects in laboratory animals, and may aggravate pre-existing disorders of these organs in humans: kidney damage, liver abnormalities, testis damage.

Ethylene glycol monobutyl ether has caused red blood hemolysis in laboratory animals and secondary injury to the kidney and liver. However, humans appear to be resistant to this effect.

Ethylene glycol monobutyl ether has been observed to cause fetotoxic effects in animal experiments in the presence of maternal toxicity. Chronic inhalation of ethylene glycol monobutyl ether has led to increased tumor production in animals.

Prolonged inhalation of iron oxide dust is known to produce a condition known as siderosis. On X-rays it appears to be a benign pneumoconiosis and is not associated with pulmonary fibrosis or disability unless there is concurrent exposure to other fibrosis producing materials such as silica. Because this product is a free-flowing liquid or paste, dust inhalation is not an expected route of exposure.

3. COMPOSITION/INFORMATION ON INGREDIENTS**Information on ingredients / Hazardous components**

Copper phthalocyanine			
CAS-No.	147-14-8	Percent (Wt./ Wt.)	10 - 30 %
C.I. Pigment Yellow 42 (Iron oxide)			
CAS-No.	51274-00-1	Percent (Wt./ Wt.)	1 - 5 %
2-(2-methoxyethoxy)ethanol; diethylene glycol monomethyl ether			
CAS-No.	111-77-3	Percent (Wt./ Wt.)	1 - 5 %
NJTSR No.56705700001-5020P			
CAS-No.	Trade Secret	Percent (Wt./ Wt.)	1 - 5 %
2-butoxyethanol; ethylene glycol monobutyl ether			
CAS-No.	111-76-2	Percent (Wt./ Wt.)	0.1 - 1 %

Other information

This material is classified as hazardous under OSHA regulations.

MATERIAL SAFETY DATA SHEET

896-7201 CHROMA-CHEM® PHTHALO BLUE

APB



Material no.		Version	2.29 / US
Specification	139542	Revision date	08/27/2011
Order Number		Print Date	04/06/2013
		Page	3 / 9

4. FIRST AID MEASURES

Inhalation

Remove to fresh air.

Cardiopulmonary resuscitation if victim is unconscious, not breathing and heart has stopped beating (no audible heartbeat, no pulse).

Seek medical advice immediately.

Skin contact

Wash contaminated area with lukewarm gently flowing water for at least 20-30 minutes. Remove contaminated clothing, shoes and leather goods under running water. If symptoms develop or persist, obtain medical attention. Wash clothing before reuse.

Eye contact

In case of contact, immediately flush eyes with plenty of water for at least 30 minutes, while holding eyelids apart.

Do not allow contaminated water to contact the unaffected eye or face during irrigation of an affected eye.

Consult a physician immediately.

Ingestion

Do not induce vomiting.

Should vomiting occur, be sure to keep victim's head below hips to avoid aspiration of vomitus into the lungs.

Rinse out mouth with water. Consult a physician.

Never administer anything by mouth to an individual who rapidly losing consciousness, unconscious or convulsing.

5. FIRE-FIGHTING MEASURES

Flash point not determined

Suitable extinguishing media

Use water spray or fog, foam, dry chemical or CO₂.

Specific hazards during fire fighting

Burning will produce toxic fumes. Burning will produce hazardous compounds including oxides of: carbon. nitrogen.

Further information

Containers can build up pressure if exposed to heat (fire). Cool with water spray. As in any fire, wear self-contained positive-pressure breathing apparatus, (MSHA/NIOSH approved or equivalent) and full protective gear.

MATERIAL SAFETY DATA SHEET

896-7201 CHROMA-CHEM® PHTHALO BLUE

APB



Material no.		Version	2.29 / US
Specification	139542	Revision date	08/27/2011
Order Number		Print Date	04/06/2013
		Page	4 / 9

6. ACCIDENTAL RELEASE MEASURES

Additional advice

Absorb spill with inert material, then place in a chemical waste container. After removal, flush contaminated area with water and collect for disposal. Clean up spills immediately. Remove sources of ignition and ventilate area. Use a respirator and other protective equipment as outlined in Section 8. Obey relevant local, state, provincial and federal laws and regulations. Do not contaminate any lakes, streams, ponds, groundwater or soil.

7. HANDLING AND STORAGE

Handling

Safe handling advice

Wash thoroughly after handling.
Use with adequate ventilation.
Follow all MSDS/label precautions even after container is emptied because it may retain product residues.
Avoid contact with skin and eyes.

Storage

Requirements for storage areas and containers

Keep away from heat. Keep away from sparks, flame and other sources of ignition.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Component occupational exposure guidelines

• 2-butoxyethanol; ethylene glycol monobutyl ether

CAS-No. 111-76-2
Control parameters 20 ppm
50 ppm
240 mg/m3

Time Weighted Average (TWA):(ACGIH)
PEL:(OSHA Z1)

Skin designation:(OSHA Z1)

Can be absorbed through the skin.

20 ppm
97 mg/m3

Time Weighted Average (TWA)
Permissible Exposure Limit (PEL):(US CA
OEL)

Skin designation:(US CA OEL)

Can be absorbed through the skin.

Engineering measures

Local exhaust and mechanical ventilation recommended.

MATERIAL SAFETY DATA SHEET**896-7201 CHROMA-CHEM® PHTHALO BLUE****APB**

Material no.		Version	2.29 / US
Specification	139542	Revision date	08/27/2011
Order Number		Print Date	04/06/2013
		Page	5 / 9

Personal protective equipment**Respiratory protection**

A respiratory protection program that meets OSHA 1910.134 and ANSI Z88.2 or applicable federal/provincial requirements must be followed whenever workplace conditions warrant respirator use. NIOSH's "Respirator Decision Logic" may be useful in determining the suitability of various types of respirators.

Hand protection

Use impermeable gloves.

Eye protection

Use chemical splash goggles or face shield.

Skin and body protection

To identify additional Personal Protective Equipment (PPE) requirements, it is recommended that a hazard assessment in accordance with the OSHA PPE Standard (29CFR1910.132) be conducted before using this product.

A safety shower and eye wash fountain should be readily available.

9. PHYSICAL AND CHEMICAL PROPERTIES**Appearance**

Form	paste
Color	blue
Odor	Mild acrylic odor.

Safety data

pH	8.0 - 9.5
Boiling point/range	> 100 °C
Flash point	not determined
Relative density	1.065 - 1.1161
Solubility/qualitative	Solubility in water: Appreciable.
Viscosity, dynamic	70 - 95 KU (25 °C)
Relative vapor density	Heavier than air
Solvents and Volatiles Data	% VOC (gm/l) 204
Evaporation rate	Slower than butyl acetate

10. STABILITY AND REACTIVITY

Materials to avoid	oxidizing substances
--------------------	----------------------

MATERIAL SAFETY DATA SHEET**896-7201 CHROMA-CHEM® PHTHALO BLUE APB**

Material no.		Version	2.29 / US
Specification	139542	Revision date	08/27/2011
Order Number		Print Date	04/06/2013
		Page	6 / 9

Further information

Stable under normal conditions.

11. TOXICOLOGICAL INFORMATION

Product Acute oral toxicity	LD50 Rat: min. 2000 mg/kg The data are derived from the evaluations or test results achieved with similar products (conclusion by analogy).
Product Acute inhalation toxicity	LC50 Rat: min. 2.53 mg/l / 4 h The data are derived from the evaluations or test results achieved with similar products (conclusion by analogy).
Product Acute dermal toxicity	LD50 Rat: min. 2000 mg/kg The data are derived from the evaluations or test results achieved with similar products (conclusion by analogy).
Component Skin irritation	2-butoxyethanol; ethylene glycol monobutyl ether 111-76-2 Rabbit / 24 h Irritating to skin. Severe skin irritation Method: Draize Test irritating
Component Eye irritation	NJTSR No.56705700001-5020P Trade Secret corrosive 2-butoxyethanol; ethylene glycol monobutyl ether 111-76-2 Rabbit Irritating to eyes. Severe eye damage must be expected. Severe eye irritation
Component Repeated dose toxicity	C.I. Pigment Yellow 42 (Iron oxide) 51274-00-1 Prolonged inhalation of iron oxide dust is known to produce a condition known as siderosis. On X-rays it appears to be a benign pneumoconiosis and is not associated with pulmonary fibrosis or disability unless there is concurrent exposure to other fibrosis producing materials such as silica. 2-butoxyethanol; ethylene glycol monobutyl ether 111-76-2 inhalative mouse Testing period: 730 d LOAEL: 0.6025 mg/l target organ/effect: Lungs, Liver
Component carcinogenicity assessment	2-butoxyethanol; ethylene glycol monobutyl ether 111-76-2 Ethylene glycol monobutyl ether has caused malignant and benign tumors in animal experiments.

MATERIAL SAFETY DATA SHEET**896-7201 CHROMA-CHEM® PHTHALO BLUE****APB**

Material no.		Version	2.29 / US
Specification	139542	Revision date	08/27/2011
Order Number		Print Date	04/06/2013
		Page	7 / 9

Component teratogenicity assessment

2-(2-methoxyethoxy)ethanol; diethylene glycol monomethyl ether
111-77-3

Diethylene glycol monomethyl ether has been shown to cause fetotoxicity and teratogenicity via oral route in tests on laboratory animals.

Product General Toxicity Information

The toxicological properties of this product were based on data from an analogous product.

Ethylene glycol monobutyl ether has caused red blood hemolysis in laboratory animals and secondary injury to the kidney and liver. However, humans appear to be resistant to this effect.

12. ECOLOGICAL INFORMATION

General Ecological Information No ecotoxicological studies are available.

13. DISPOSAL CONSIDERATIONS**WASTE DISPOSAL**

Advice on disposal Waste must be disposed of in accordance with federal, state, provincial and local regulations.

14. TRANSPORT INFORMATION**Transport/further information**

Not dangerous according to transport regulations.

15. REGULATORY INFORMATION**US Federal Regulations****OSHA**

If listed below, chemical specific standards apply to the product or components:

- None listed

Clean Air Act Section (112)

If listed below, components present at or above the de minimus level are hazardous air pollutants:

- 2-(2-methoxyethoxy)ethanol; diethylene glycol monomethyl ether
CAS-No. 111-77-3

MATERIAL SAFETY DATA SHEET

896-7201 CHROMA-CHEM® PHTHALO BLUE APB



Material no.		Version	2.29 / US
Specification	139542	Revision date	08/27/2011
Order Number		Print Date	04/06/2013
		Page	8 / 9

CERCLA Reportable Quantities

If listed below, a reportable quantity (RQ) applies to the product based on the percent of the named component:

- None listed

SARA Title III Section 311/312 Hazard Categories

The product meets the criteria only for the listed hazard classes:

- Acute Health Hazard
- Chronic Health Hazard

SARA Title III Section 313 Reportable Substances

If listed below, components are subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

- 2-butoxyethanol; ethylene glycol monobutyl ether
CAS-No. 111-76-2
- 2-(2-methoxyethoxy)ethanol; diethylene glycol monomethyl ether
CAS-No. 111-77-3

Toxic Substances Control Act (TSCA)

If listed below, non-proprietary substances are subject to export notification under Section 12 (b) of TSCA:

- None listed

State Regulations

California Proposition 65

A warning under the California Drinking Water Act is required only if listed below:

- None listed

MATERIAL SAFETY DATA SHEET

896-7201 CHROMA-CHEM® PHTHALO BLUE

APB



Material no.		Version	2.29 / US
Specification	139542	Revision date	08/27/2011
Order Number		Print Date	04/06/2013
		Page	9 / 9

International Chemical Inventory Status

Unless otherwise noted, this product is in compliance with the inventory listing of the countries shown below. For information on listing for countries not shown, contact the Product Regulatory Services Department.

• Europe (EINECS/ELINCS)	Listed/registered
• USA (TSCA)	Listed/registered
• Canada (DSL)	Admitted with restrictions
• Australia (AICS)	Not listed/Not registered
• Japan (MITI)	Not listed/Not registered
• Korea (TCCL)	Not listed/Not registered
• Philippines (PICCS)	Not listed/Not registered
• China	Listed/registered
• New Zealand	Not listed/Not registered

16. OTHER INFORMATION

HMIS Ratings

Health :	2*
Flammability :	1
Physical Hazard :	0

Further information

Changes since the last version are highlighted in the margin. This version replaces all previous versions.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.