

1. Identification

Product identifier MAXIMUS SOLVENTBORNE EPOXY - DEEP BASE

Other means of identification

Product code 51844D

Recommended use Industrial applications.

Recommended restrictions Professional use only

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name Ellis Paint Company
Address 3150 E. Pico Blvd.
Los Angeles, CA 90023-3683
United States

Telephone Customer Service (800) 672-4900

Website www.ellispaint.com

E-mail info@ellispaint.com

Emergency phone number CHEMTREC (800) 424-9300

2. Hazard(s) identification

Physical hazards Flammable liquids Category 3

Health hazards Carcinogenicity Category 1A

Environmental hazards Not classified.

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Flammable liquid and vapor. May cause cancer.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wear protective gloves/protective clothing/eye protection/face protection.

Response If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If exposed or concerned: Get medical advice/attention. In case of fire: Use appropriate media to extinguish.

Storage Store in a well-ventilated place. Keep cool. Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC) None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

| Chemical name | Common name and synonyms | CAS number | % |
|---------------------------|--------------------------|------------|-----------|
| CRYSTALLINE SILICA QUARTZ | | 14808-60-7 | 30 - < 40 |

| Chemical name | Common name and synonyms | CAS number | % |
|---------------------------------|--------------------------|------------|-----------|
| PCBTf, P-Chlorobenzotrifluoride | | 98-56-6 | 10 - < 20 |
| TITANIUM DIOXIDE | | 13463-67-7 | 10 - < 20 |
| METHYL ETHYL KETONE(MEK) | | 78-93-3 | 1 - < 3 |
| CRYSTALLINE SILICA | | 14464-46-1 | < 1 |
| METHYL ISOBUTYL KETONE(MIBK) | | 108-10-1 | < 1 |

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. First-aid measures

| | |
|---|---|
| Inhalation | Move to fresh air. Call a physician if symptoms develop or persist. |
| Skin contact | Take off immediately all contaminated clothing. Rinse skin with water/shower. Get medical attention if irritation develops and persists. |
| Eye contact | Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Get medical attention if irritation develops and persists. |
| Ingestion | Rinse mouth. Get medical attention if symptoms occur. |
| Most important symptoms/effects, acute and delayed | Direct contact with eyes may cause temporary irritation. Coughing. |
| Indication of immediate medical attention and special treatment needed | Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed. |
| General information | Take off all contaminated clothing immediately. IF exposed or concerned: Get medical advice/attention. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse. |

5. Fire-fighting measures

| | |
|--|--|
| Suitable extinguishing media | Water fog. Foam. Dry chemical powder. Carbon dioxide (CO ₂). |
| Unsuitable extinguishing media | Do not use water jet as an extinguisher, as this will spread the fire. |
| Specific hazards arising from the chemical | Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed. |
| Special protective equipment and precautions for firefighters | Self-contained breathing apparatus and full protective clothing must be worn in case of fire. |
| Fire fighting equipment/instructions | In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk. |
| Specific methods | Use standard firefighting procedures and consider the hazards of other involved materials. |
| General fire hazards | Flammable liquid and vapor. |

6. Accidental release measures

| | |
|--|---|
| Personal precautions, protective equipment and emergency procedures | Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS. |
|--|---|

Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Take precautionary measures against static discharge. Use only non-sparking tools. Keep combustibles (wood, paper, oil, etc.) away from spilled material.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground.

Environmental precautions**7. Handling and storage****Precautions for safe handling**

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid prolonged exposure. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection**Occupational exposure limits****US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)**

| Components | Type | Value | Form |
|---|------|----------------------|-------------|
| METHYL ETHYL KETONE(MEK) (CAS 78-93-3) | PEL | 590 mg/m3 | |
| METHYL ISOBUTYL KETONE(MIBK) (CAS 108-10-1) | PEL | 200 ppm 410 mg/m3 | |
| TITANIUM DIOXIDE (CAS 13463-67-7) | PEL | 100 ppm 15 mg/m3 | Total dust. |

US. OSHA Table Z-3 (29 CFR 1910.1000)

| Components | Type | Value | Form |
|--|------|------------|-------------|
| CRYSTALLINE SILICA (CAS 14464-46-1) | TWA | 0.15 mg/m3 | Total dust. |
| CRYSTALLINE SILICA QUARTZ (CAS 14808-60-7) | TWA | 0.05 mg/m3 | Respirable. |
| | | 1.2 mppcf | Respirable. |
| | | 0.3 mg/m3 | Total dust. |
| | | 0.1 mg/m3 | Respirable. |
| | | 2.4 mppcf | Respirable. |

US. ACGIH Threshold Limit Values

| Components | Type | Value | Form |
|--|------|-------------|----------------------|
| CRYSTALLINE SILICA (CAS 14464-46-1) | TWA | 0.025 mg/m3 | Respirable fraction. |
| CRYSTALLINE SILICA QUARTZ (CAS 14808-60-7) | TWA | 0.025 mg/m3 | Respirable fraction. |
| METHYL ETHYL KETONE(MEK) (CAS 78-93-3) | STEL | 300 ppm | |

US. ACGIH Threshold Limit Values

| Components | Type | Value | Form |
|---|------|----------|------|
| METHYL ISOBUTYL KETONE(MIBK) (CAS 108-10-1) | TWA | 200 ppm | |
| | STEL | 75 ppm | |
| TITANIUM DIOXIDE (CAS 13463-67-7) | TWA | 20 ppm | |
| | TWA | 10 mg/m3 | |

US. NIOSH: Pocket Guide to Chemical Hazards

| Components | Type | Value | Form |
|---|------|--------------|--------------------|
| CRYSTALLINE SILICA (CAS 14464-46-1) | TWA | 3 fibers/cm3 | Dust. |
| | | 3 fibers/cm3 | Fiber. |
| | | 5 mg/m3 | fibers, total dust |
| | | 5 mg/m3 | Fiber, total |
| CRYSTALLINE SILICA QUARTZ (CAS 14808-60-7) | TWA | 0.05 mg/m3 | Respirable dust. |
| | | 885 mg/m3 | |
| METHYL ETHYL KETONE(MEK) (CAS 78-93-3) | TWA | 300 ppm | |
| | | 590 mg/m3 | |
| METHYL ISOBUTYL KETONE(MIBK) (CAS 108-10-1) | STEL | 200 ppm | |
| | | 300 mg/m3 | |
| | TWA | 75 ppm | |
| | | 205 mg/m3 | |
| | | 50 ppm | |

Biological limit values**ACGIH Biological Exposure Indices**

| Components | Value | Determinant | Specimen | Sampling Time |
|---|--------|------------------------|----------|---------------|
| METHYL ETHYL KETONE(MEK) (CAS 78-93-3) | 2 mg/l | MEK | Urine | * |
| METHYL ISOBUTYL KETONE(MIBK) (CAS 108-10-1) | 1 mg/l | Methyl isobutyl ketone | Urine | * |

* - For sampling details, please see the source document.

Appropriate engineering controls

Explosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

| | |
|-------------------------------|---|
| Eye/face protection | Chemical respirator with organic vapor cartridge and full facepiece. |
| Skin protection | |
| Hand protection | Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier. |
| Other | Wear suitable protective clothing. Use of an impervious apron is recommended. |
| Respiratory protection | Chemical respirator with organic vapor cartridge and full facepiece. |
| Thermal hazards | Wear appropriate thermal protective clothing, when necessary. |

General hygiene considerations

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties**Appearance**

| | |
|---|---|
| Physical state | Liquid. |
| Form | Liquid. |
| Color | White. |
| Odor | Characteristic. |
| Odor threshold | Not available. |
| pH | Not available. |
| Melting point/freezing point | -32.8 °F (-36 °C) estimated |
| Initial boiling point and boiling range | 282 °F (138.89 °C) estimated |
| Flash point | 109.0 °F (42.8 °C) estimated |
| Evaporation rate | Not available. |
| Flammability (solid, gas) | Not applicable. |
| Upper/lower flammability or explosive limits | |
| Flammability limit - lower (%) | Not available. |
| Flammability limit - upper (%) | Not available. |
| Explosive limit - lower (%) | Not available. |
| Explosive limit - upper (%) | Not available. |
| Vapor pressure | 8.62 hPa estimated |
| Vapor density | Not available. |
| Relative density | Not available. |
| Solubility(ies) | |
| Solubility (water) | Not available. |
| Partition coefficient (n-octanol/water) | Not available. |
| Auto-ignition temperature | Not available. |
| Decomposition temperature | Not available. |
| Viscosity | Not available. |
| Other information | |
| Density | 13.62 lbs/gal |
| Explosive properties | Not explosive. |
| Flammability class | Combustible II estimated |
| Oxidizing properties | Not oxidizing. |
| Percent volatile | 16 % estimated |
| Specific gravity | 1.64 |
| VOC | 0.48 lbs/gal (57.60 g/l) Coating VOC 0.4 lbs/gal (48.12 g/l) Material VOC 0.55 lbs/gal (65.71 g/l) Coating VOC as applied 0.45 lbs/gal (53.78 g/l) Material VOC as applied |

10. Stability and reactivity

| | |
|---|--|
| Reactivity | The product is stable and non-reactive under normal conditions of use, storage and transport. |
| Chemical stability | Material is stable under normal conditions. |
| Possibility of hazardous reactions | Hazardous polymerization does not occur. |
| Conditions to avoid | Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials. |
| Incompatible materials | Powerful oxidizers. Chlorine. |
| Hazardous decomposition products | No hazardous decomposition products are known. |

11. Toxicological information

Information on likely routes of exposure

| | |
|---------------------|--|
| Inhalation | Prolonged inhalation may be harmful. |
| Skin contact | No adverse effects due to skin contact are expected. |
| Eye contact | Direct contact with eyes may cause temporary irritation. |
| Ingestion | Expected to be a low ingestion hazard. |

Symptoms related to the physical, chemical and toxicological characteristics Coughing.

Information on toxicological effects

Acute toxicity

| Components | Species | Test Results |
|---|---------|---|
| METHYL ETHYL KETONE(MEK) (CAS 78-93-3) | | |
| Acute | | |
| Dermal | | |
| LD50 | Rabbit | > 8000 mg/kg |
| Inhalation | | |
| LC50 | Mouse | 11000 ppm, 45 Minutes |
| | Rat | 11700 ppm, 4 Hours |
| Oral | | |
| LD50 | Mouse | 670 mg/kg |
| | Rat | 2300 - 3500 mg/kg |
| METHYL ISOBUTYL KETONE(MIBK) (CAS 108-10-1) | | |
| Acute | | |
| Dermal | | |
| LD50 | Rabbit | > 16000 mg/kg |
| Inhalation | | |
| LC50 | Rat | 8.2 mg/l, 4 Hours |
| Oral | | |
| LD50 | Rat | 2080 mg/kg |
| PCBTF, P-Chlorobenzotrifluoride (CAS 98-56-6) | | |
| Acute | | |
| Dermal | | |
| LD50 | Rabbit | > 2000 mg/kg |
| Inhalation | | |
| LC50 | Rat | 4468 ppm, 4 hours (vapor) 33 mg/l, 4 hours (vapor) |
| Oral | | |
| LD50 | Rat | 13000 mg/kg |

* Estimates for product may be based on additional component data not shown.

| | |
|--|--|
| Skin corrosion/irritation | Prolonged skin contact may cause temporary irritation. |
| Serious eye damage/eye irritation | Direct contact with eyes may cause temporary irritation. |
| Respiratory or skin sensitization | |
| Respiratory sensitization | Not a respiratory sensitizer. |
| Skin sensitization | This product is not expected to cause skin sensitization. |
| Germ cell mutagenicity | No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic. |
| Carcinogenicity | May cause cancer. |

IARC Monographs. Overall Evaluation of Carcinogenicity

| | |
|---|-------------------------------------|
| CRYSTALLINE SILICA (CAS 14464-46-1) | 1 Carcinogenic to humans. |
| CRYSTALLINE SILICA QUARTZ (CAS 14808-60-7) | 1 Carcinogenic to humans. |
| METHYL ISOBUTYL KETONE(MIBK) (CAS 108-10-1) | 2B Possibly carcinogenic to humans. |
| TITANIUM DIOXIDE (CAS 13463-67-7) | 2B Possibly carcinogenic to humans. |

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

US. National Toxicology Program (NTP) Report on Carcinogens

| | |
|--|--|
| CRYSTALLINE SILICA (CAS 14464-46-1) | Known To Be Human Carcinogen. |
| | Reasonably Anticipated to be a Human Carcinogen. |
| CRYSTALLINE SILICA QUARTZ (CAS 14808-60-7) | Known To Be Human Carcinogen. |

| | |
|---|--|
| Reproductive toxicity | This product is not expected to cause reproductive or developmental effects. |
| Specific target organ toxicity - single exposure | Not classified. |
| Specific target organ toxicity - repeated exposure | Not classified. |
| Aspiration hazard | Not an aspiration hazard. |
| Chronic effects | Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects. |

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

| Components | Species | Test Results |
|---|---------|--|
| METHYL ETHYL KETONE(MEK) (CAS 78-93-3) | | |
| Aquatic | | |
| Crustacea | EC50 | Water flea (Daphnia magna) 4025 - 6440 mg/l, 48 hours |
| Fish | LC50 | Sheepshead minnow (Cyprinodon variegatus) > 400 mg/l, 96 hours |
| METHYL ISOBUTYL KETONE(MIBK) (CAS 108-10-1) | | |
| Aquatic | | |
| Fish | LC50 | Fathead minnow (Pimephales promelas) 492 - 593 mg/l, 96 hours |
| PCBTF, P-Chlorobenzotrifluoride (CAS 98-56-6) | | |
| Aquatic | | |
| <i>Acute</i> | | |
| Algae | EC50 | Green algae (Chlamydomonas variabilis) > 0.41 mg/l, 72 hours |
| Crustacea | EC50 | Daphnia magna 2 mg/l, 48 hours |
| Fish | EC50 | Zebra danio (Danio rerio) 3 mg/l, 96 hours |
| <i>Chronic</i> | | |
| Algae | NOEC | Green algae (Chlamydomonas variabilis) 0.41 mg/l, 21 days |
| TITANIUM DIOXIDE (CAS 13463-67-7) | | |
| Aquatic | | |
| Crustacea | EC50 | Water flea (Daphnia magna) > 1000 mg/l, 48 hours |
| Fish | LC50 | Mummichog (Fundulus heteroclitus) > 1000 mg/l, 96 hours |

* Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

| | |
|---------------------------------|------|
| METHYL ETHYL KETONE(MEK) | 0.29 |
| METHYL ISOBUTYL KETONE(MIBK) | 1.38 |
| PCBTF, P-Chlorobenzotrifluoride | 3.7 |

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

| | |
|--|--|
| Disposal instructions | Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations. |
| Local disposal regulations | Dispose in accordance with all applicable regulations. |
| Hazardous waste code | The waste code should be assigned in discussion between the user, the producer and the waste disposal company. |
| Waste from residues / unused products | Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions). |
| Contaminated packaging | Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. |

14. Transport information

| | |
|---|--|
| DOT | |
| UN number | UN1263 |
| UN proper shipping name | Paint including paint, lacquer, enamel, stain, shellac solutions, varnish, polish, liquid filler, and liquid lacquer base |
| Transport hazard class(es) | |
| Class | 3 |
| Subsidiary risk | - |
| Label(s) | 3 |
| Packing group | III |
| Special precautions for user | Read safety instructions, SDS and emergency procedures before handling. |
| Special provisions | B1, B52, IB3, T2, TP1, TP29 |
| Packaging exceptions | 150 |
| Packaging non bulk | 173 |
| Packaging bulk | 242 |
| IATA | |
| UN number | UN1263 |
| UN proper shipping name | Paint (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) |
| Transport hazard class(es) | |
| Class | 3 |
| Subsidiary risk | - |
| Packing group | III |
| Environmental hazards | Yes |
| ERG Code | 3L |
| Special precautions for user | Read safety instructions, SDS and emergency procedures before handling. |
| Other information | |
| Passenger and cargo aircraft | Allowed. |
| Cargo aircraft only | Allowed. |
| IMDG | |
| UN number | UN1263 |
| UN proper shipping name | PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound) |
| Transport hazard class(es) | |
| Class | 3 |
| Subsidiary risk | - |
| Packing group | III |
| Environmental hazards | |
| Marine pollutant | Yes |
| EmS | F-E, <u>S</u> -E |
| Special precautions for user | Read safety instructions, SDS and emergency procedures before handling. |
| Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code | Not established. |


DOT



IATA; IMDG



Marine pollutant



General information

IMDG Regulated Marine Pollutant.

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

PCBTf, P-Chlorobenzotrifluoride (CAS 98-56-6) 1.0 % One-Time Export Notification only.

CERCLA Hazardous Substance List (40 CFR 302.4)

METHYL ETHYL KETONE(MEK) (CAS 78-93-3) Listed.

METHYL ISOBUTYL KETONE(MIBK) (CAS 108-10-1) Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Immediate Hazard - No
Delayed Hazard - Yes
Fire Hazard - Yes
Pressure Hazard - No
Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical No

SARA 313 (TRI reporting)

| Chemical name | CAS number | % by wt. |
|------------------------------|------------|----------|
| METHYL ISOBUTYL KETONE(MIBK) | 108-10-1 | < 1 |

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

METHYL ISOBUTYL KETONE(MIBK) (CAS 108-10-1)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Not regulated.

Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number

METHYL ETHYL KETONE(MEK) (CAS 78-93-3) 6714

METHYL ISOBUTYL KETONE(MIBK) (CAS 108-10-1) 6715

Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

METHYL ETHYL KETONE(MEK) (CAS 78-93-3) 35 %WV

METHYL ISOBUTYL KETONE(MIBK) (CAS 108-10-1) 35 %WV

DEA Exempt Chemical Mixtures Code Number

METHYL ETHYL KETONE(MEK) (CAS 78-93-3) 6714

METHYL ISOBUTYL KETONE(MIBK) (CAS 108-10-1) 6715

US state regulations

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed.

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

CRYSTALLINE SILICA (CAS 14464-46-1)

CRYSTALLINE SILICA QUARTZ (CAS 14808-60-7)

METHYL ETHYL KETONE(MEK) (CAS 78-93-3)

METHYL ISOBUTYL KETONE(MIBK) (CAS 108-10-1)

TITANIUM DIOXIDE (CAS 13463-67-7)

US. Massachusetts RTK - Substance List

CRYSTALLINE SILICA (CAS 14464-46-1)

CRYSTALLINE SILICA QUARTZ (CAS 14808-60-7)

METHYL ETHYL KETONE(MEK) (CAS 78-93-3)

METHYL ISOBUTYL KETONE(MIBK) (CAS 108-10-1)

TITANIUM DIOXIDE (CAS 13463-67-7)

US. New Jersey Worker and Community Right-to-Know Act

CRYSTALLINE SILICA (CAS 14464-46-1)

CRYSTALLINE SILICA QUARTZ (CAS 14808-60-7)

METHYL ETHYL KETONE(MEK) (CAS 78-93-3)

METHYL ISOBUTYL KETONE(MIBK) (CAS 108-10-1)

PCBTF, P-Chlorobenzotrifluoride (CAS 98-56-6)

TITANIUM DIOXIDE (CAS 13463-67-7)

US. Pennsylvania Worker and Community Right-to-Know Law

CRYSTALLINE SILICA (CAS 14464-46-1)

CRYSTALLINE SILICA QUARTZ (CAS 14808-60-7)

METHYL ETHYL KETONE(MEK) (CAS 78-93-3)

METHYL ISOBUTYL KETONE(MIBK) (CAS 108-10-1)

TITANIUM DIOXIDE (CAS 13463-67-7)

US. Rhode Island RTK

METHYL ETHYL KETONE(MEK) (CAS 78-93-3)

METHYL ISOBUTYL KETONE(MIBK) (CAS 108-10-1)

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

CRYSTALLINE SILICA QUARTZ (CAS 14808-60-7) Listed: October 1, 1988

METHYL ISOBUTYL KETONE(MIBK) (CAS 108-10-1) Listed: November 4, 2011

TITANIUM DIOXIDE (CAS 13463-67-7) Listed: September 2, 2011

US - California Proposition 65 - CRT: Listed date/Developmental toxin

METHYL ISOBUTYL KETONE(MIBK) (CAS
108-10-1)

Listed: March 28, 2014

International Inventories

| Country(s) or region | Inventory name | On inventory (yes/no)* |
|-----------------------------|---|------------------------|
| United States & Puerto Rico | Toxic Substances Control Act (TSCA) Inventory | Yes |

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

| | |
|---------------|---|
| Issue date | 01-25-2016 |
| Version # | 01 |
| HMIS® ratings | Health: 1* Flammability: 3 Physical hazard: 0 |
| NFPA ratings | Health: 1 Flammability: 3 Instability: 0 |

NFPA ratings



Disclaimer

The information contained herein is based on data supplied to us from sources believed to be reliable at the date of issue. Nothing herein shall be deemed to create any warranty of any kind, express or implied, concerning the accuracy or completeness of the information provided or the results to be obtained from the use thereof. It is offered for your consideration, investigation and verification. Buyer assumes all risk of use, storage, transportation, handling and disposal of the product in compliance with applicable federal, state and local laws and regulations. This information relates to the material designated and may not be valid for such material used in combination with any other materials nor in any process.