

1. Identification

Product identifier	SHAFT LAC ENAMEL - SATIN BLACK	
Other means of identification		
Product code	3396	
Recommended use	Industrial applications.	
Recommended restrictions	Professional use only	
Manufacturer/Importer/Supplier/Distributor information		
Manufacturer		
Company name	Ellis Paint Company	
Address	3150 E. Pico Blvd. Los Angeles, CA 90023-3683 United States	
Telephone	Customer Service	(800) 672-4900
Website	www.ellispaint.com	
E-mail	info@ellispaint.com	
Emergency phone number	CHEMTREC	(800) 424-9300

2. Hazard(s) identification

Physical hazards	Flammable liquids	Category 2
Health hazards	Skin corrosion/irritation	Category 2
	Serious eye damage/eye irritation	Category 2A
	Sensitization, skin	Category 1
	Germ cell mutagenicity	Category 1B
	Carcinogenicity	Category 1B
	Reproductive toxicity (the unborn child)	Category 2
	Specific target organ toxicity, single exposure	Category 3 narcotic effects
	Specific target organ toxicity, repeated exposure	Category 1
Environmental hazards	Not classified.	
OSHA defined hazards	Not classified.	

Label elements



Signal word	Danger
Hazard statement	Highly flammable liquid and vapor. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. May cause drowsiness or dizziness. May cause genetic defects. May cause cancer. Suspected of damaging the unborn child. Causes damage to organs through prolonged or repeated exposure.
Precautionary statement	
Prevention	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe mist or vapor. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Contaminated work clothing must not be allowed out of the workplace. Wear eye protection/face protection. Wear protective gloves/protective clothing/eye protection/face protection.

Response	If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash before reuse. In case of fire: Use appropriate media to extinguish.
Storage	Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.
Hazard(s) not otherwise classified (HNOC)	Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion.
Supplemental information	None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
ACETONE		67-64-1	10 - < 20
PCBTF, P-Chlorobenzotrifluoride		98-56-6	10 - < 20
SILICON DIOXIDE		112926-00-8	5 - < 10
SOLVENT NAPHTHA (PETROLEUM), LIGHT AROMATIC		64742-95-6	5 - < 10
DIMETHYLBENZENE (MIXED ISOMERS)		1330-20-7	3 - < 5
MINERAL SPIRITS		64742-88-7	3 - < 5
CARBON BLACK		1333-86-4	1 - < 3
TRIMETHYLBENZENE		25551-13-7	1 - < 3
ETHYLBENZENE		100-41-4	< 1
2-BUTANONE OXIME		96-29-7	< 0.2

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
Skin contact	Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema or other skin disorders: Seek medical attention and take along these instructions. Wash contaminated clothing before reuse.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Ingestion	Rinse mouth. Get medical attention if symptoms occur.
Most important symptoms/effects, acute and delayed	May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash. Prolonged exposure may cause chronic effects.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.
General information	Take off all contaminated clothing immediately. IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media	Alcohol resistant foam. Water fog. Carbon dioxide (CO2). Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.
-------------------------------------	---

Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. This product is a poor conductor of electricity and can become electrostatically charged. If sufficient charge is accumulated, ignition of flammable mixtures can occur. To reduce potential for static discharge, use proper bonding and grounding procedures. This liquid may accumulate static electricity when filling properly grounded containers. Static electricity accumulation may be significantly increased by the presence of small quantities of water or other contaminants. Material will float and may ignite on surface of water. During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	Highly flammable liquid and vapor.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Use appropriate containment to avoid environmental contamination. Transfer by mechanical means such as vacuum truck to a salvage tank or other suitable container for recovery or safe disposal. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Take precautionary measures against static discharge. Use only non-sparking tools. Keep combustibles (wood, paper, oil, etc.) away from spilled material.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

Environmental precautions Avoid discharge into drains, water courses or onto the ground. Use appropriate containment to avoid environmental contamination.

7. Handling and storage

Precautions for safe handling Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Explosion-proof general and local exhaust ventilation. Minimize fire risks from flammable and combustible materials (including combustible dust and static accumulating liquids) or dangerous reactions with incompatible materials. Handling operations that can promote accumulation of static charges include but are not limited to: mixing, filtering, pumping at high flow rates, splash filling, creating mists or sprays, tank and container filling, tank cleaning, sampling, gauging, switch loading, vacuum truck operations. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Do not breathe mist or vapor. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. When using, do not eat, drink or smoke. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.

For additional information on equipment bonding and grounding, refer to the Canadian Electrical Code in Canada, (CSA C22.1), or the American Petroleum Institute (API) Recommended Practice 2003, "Protection Against Ignitions Arising out of Static, Lightning, and Stray Currents" or National Fire Protection Association (NFPA) 77, "Recommended Practice on Static Electricity" or National Fire Protection Association (NFPA) 70, "National Electrical Code".

Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Eliminate sources of ignition. Avoid spark promoters. Ground/bond container and equipment. These alone may be insufficient to remove static electricity. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection**Occupational exposure limits****US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)**

Components	Type	Value
ACETONE (CAS 67-64-1)	PEL	2400 mg/m ³ 1000 ppm
CARBON BLACK (CAS 1333-86-4)	PEL	3.5 mg/m ³
DIMETHYLBENZENE (MIXED ISOMERS) (CAS 1330-20-7)	PEL	435 mg/m ³
ETHYLBENZENE (CAS 100-41-4)	PEL	100 ppm 435 mg/m ³
		100 ppm

US. OSHA Table Z-3 (29 CFR 1910.1000)

Components	Type	Value
SILICON DIOXIDE (CAS 112926-00-8)	TWA	0.8 mg/m ³ 20 mppcf

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
ACETONE (CAS 67-64-1)	STEL	750 ppm	
	TWA	500 ppm	
CARBON BLACK (CAS 1333-86-4)	TWA	3 mg/m ³	Inhalable fraction.
DIMETHYLBENZENE (MIXED ISOMERS) (CAS 1330-20-7)	STEL	150 ppm	
	TWA	100 ppm	
ETHYLBENZENE (CAS 100-41-4)	TWA	20 ppm	
MINERAL SPIRITS (CAS 64742-88-7)	TWA	200 mg/m ³	Non-aerosol.
TRIMETHYLBENZENE (CAS 25551-13-7)	TWA	25 ppm	

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
ACETONE (CAS 67-64-1)	TWA	590 mg/m ³ 250 ppm
CARBON BLACK (CAS 1333-86-4)	TWA	0.1 mg/m ³
ETHYLBENZENE (CAS 100-41-4)	STEL	545 mg/m ³
	TWA	125 ppm 435 mg/m ³ 100 ppm
MINERAL SPIRITS (CAS 64742-88-7)	TWA	100 mg/m ³
SILICON DIOXIDE (CAS 112926-00-8)	TWA	6 mg/m ³

US. Workplace Environmental Exposure Level (WEEL) Guides

Components	Type	Value
2-BUTANONE OXIME (CAS 96-29-7)	TWA	36 mg/m ³ 10 ppm

Biological limit values

ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
ACETONE (CAS 67-64-1)	50 mg/l	Acetone	Urine	*
DIMETHYLBENZENE (MIXED ISOMERS) (CAS 1330-20-7)	1.5 g/g	Methylhippuric acids	Creatinine in urine	*
ETHYLBENZENE (CAS 100-41-4)	0.15 g/g	Sum of mandelic acid and phenylglyoxylic acid	Creatinine in urine	*

* - For sampling details, please see the source document.

Exposure guidelines

US ACGIH Threshold Limit Values: Skin designation

MINERAL SPIRITS (CAS 64742-88-7)

Can be absorbed through the skin.

Appropriate engineering controls

Explosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

Individual protection measures, such as personal protective equipment

Eye/face protection

Chemical respirator with organic vapor cartridge and full facepiece.

Skin protection

Hand protection

Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier.

Other

Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Respiratory protection

Chemical respirator with organic vapor cartridge and full facepiece.

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties

Appearance

Physical state

Liquid.

Form

Liquid.

Color

Black.

Odor

Characteristic.

Odor threshold

Not available.

pH

Not available.

Melting point/freezing point

-137.2 °F (-94 °C) estimated

Initial boiling point and boiling range

132.8 °F (56 °C) estimated

Flash point

-0.4 °F (-18.0 °C) estimated

Evaporation rate

Not available.

Flammability (solid, gas)

Not applicable.

Upper/lower flammability or explosive limits

Flammability limit - lower (%) 2.1 % estimated

Flammability limit - upper (%) 13 % estimated

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure 46.16 hPa estimated

Vapor density Not available.

Relative density Not available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient (n-octanol/water) Not available.

Auto-ignition temperature 860 °F (460 °C) estimated

Decomposition temperature Not available.

Viscosity Not available.

Other information

Density 8.37 lbs/gal

Explosive properties Not explosive.

Flammability class Flammable IB estimated

Oxidizing properties Not oxidizing.

Percent volatile 44 % estimated

Specific gravity 1

VOC 2.19 lbs/gal (262.81 g/l) Coating VOC

1.62 lbs/gal (194.33 g/l) Material VOC

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous reactions Hazardous polymerization does not occur.

Conditions to avoid Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.

Incompatible materials Strong acids. Acids. Strong oxidizing agents. Halogens. Fluorine. Chlorine.

Hazardous decomposition products No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation May cause damage to organs through prolonged or repeated exposure by inhalation. May cause drowsiness and dizziness. Headache. Nausea, vomiting.

Skin contact Causes skin irritation. May cause an allergic skin reaction.

Eye contact Causes serious eye irritation.

Ingestion Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics Headache. May cause drowsiness and dizziness. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.

Information on toxicological effects

Acute toxicity Narcotic effects. May cause an allergic skin reaction.

Components	Species	Test Results
ACETONE (CAS 67-64-1)		
<u>Acute</u>		
Dermal		
LD50	Rabbit	> 5000 mg/kg
Inhalation		
LC50	Rat	> 20 mg/l, 4 Hours
Oral		
LD50	Rat	> 5000 mg/kg
CARBON BLACK (CAS 1333-86-4)		
<u>Acute</u>		
Oral		
LD50	Rat	> 8000 mg/kg
DIMETHYLBENZENE (MIXED ISOMERS) (CAS 1330-20-7)		
<u>Acute</u>		
Dermal		
LD50	Rabbit	> 43 g/kg
Inhalation		
LC50	Mouse	3907 mg/l, 6 Hours
	Rat	6350 mg/l, 4 Hours
Oral		
LD50	Mouse	1590 mg/kg
	Rat	3523 - 8600 mg/kg
ETHYLBENZENE (CAS 100-41-4)		
<u>Acute</u>		
Dermal		
LD50	Rabbit	17800 mg/kg
Oral		
LD50	Rat	3500 mg/kg
PCBTF, P-Chlorobenzotrifluoride (CAS 98-56-6)		
<u>Acute</u>		
Dermal		
LD50	Rabbit	> 2000 mg/kg
Inhalation		
LC50	Rat	4468 ppm, 4 hours (vapor) 33 mg/l, 4 hours (vapor)
Oral		
LD50	Rat	13000 mg/kg
SILICON DIOXIDE (CAS 112926-00-8)		
<u>Acute</u>		
Oral		
LD50	Mouse	> 15000 mg/kg
	Rat	> 22500 mg/kg
TRIMETHYLBENZENE (CAS 25551-13-7)		
<u>Acute</u>		
Oral		
LD50	Rat	8970 mg/kg

* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye irritation Causes serious eye irritation.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization May cause an allergic skin reaction.

Germ cell mutagenicity May cause genetic defects.

Carcinogenicity May cause cancer.

IARC Monographs. Overall Evaluation of Carcinogenicity

CARBON BLACK (CAS 1333-86-4)	2B Possibly carcinogenic to humans.
DIMETHYLBENZENE (MIXED ISOMERS) (CAS 1330-20-7)	3 Not classifiable as to carcinogenicity to humans.
ETHYLBENZENE (CAS 100-41-4)	2B Possibly carcinogenic to humans.
SILICON DIOXIDE (CAS 112926-00-8)	3 Not classifiable as to carcinogenicity to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Reproductive toxicity Components in this product have been shown to cause birth defects and reproductive disorders in laboratory animals. Suspected of damaging the unborn child.

Specific target organ toxicity - single exposure May cause drowsiness and dizziness.

Specific target organ toxicity - repeated exposure Causes damage to organs through prolonged or repeated exposure.

Aspiration hazard Not an aspiration hazard.

Chronic effects Causes damage to organs through prolonged or repeated exposure. Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components	Species	Test Results
2-BUTANONE OXIME (CAS 96-29-7)		
Aquatic		
Fish	LC50	Fathead minnow (<i>Pimephales promelas</i>) 777 - 914 mg/l, 96 hours
ACETONE (CAS 67-64-1)		
<i>Acute</i>		
Other	LC50	Micro-organisms > 100 mg/l
Aquatic		
<i>Acute</i>		
Algae	LC50	Algae > 100 mg/l
Crustacea	LC50	Crustacea > 100 mg/l
Fish	LC50	Fish > 100 mg/l
<i>Chronic</i>		
Crustacea	NOEC	Crustacea 10 - 100 mg/l
DIMETHYLBENZENE (MIXED ISOMERS) (CAS 1330-20-7)		
Aquatic		
Fish	LC50	Bluegill (<i>Lepomis macrochirus</i>) 7.711 - 9.591 mg/l, 96 hours
ETHYLBENZENE (CAS 100-41-4)		
Aquatic		
Crustacea	EC50	Water flea (<i>Daphnia magna</i>) 1.37 - 4.4 mg/l, 48 hours
Fish	LC50	Fathead minnow (<i>Pimephales promelas</i>) 7.5 - 11 mg/l, 96 hours
PCBTf, P-Chlorobenzotrifluoride (CAS 98-56-6)		
Aquatic		
<i>Acute</i>		
Algae	EC50	Green algae (<i>Chlamydomonas variabilis</i>) > 0.41 mg/l, 72 hours

Components		Species	Test Results
Crustacea	EC50	Daphnia magna	2 mg/l, 48 hours
Fish	EC50	Zebra danio (Danio rerio)	3 mg/l, 96 hours
<i>Chronic</i>			
Algae	NOEC	Green algae (Chlamydomonas variabilis)	0.41 mg/l, 21 days

* Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

ACETONE	0.2, (log Pow)
DIMETHYLBENZENE (MIXED ISOMERS)	3.12 - 3.2
ETHYLBENZENE	3.15
PCBTf, P-Chlorobenzotrifluoride	3.7

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

Waste from residues / unused products Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT	
UN number	UN1263
UN proper shipping name	Paint including paint, lacquer, enamel, stain, shellac solutions, varnish, polish, liquid filler, and liquid lacquer base
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Label(s)	3
Packing group	II
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Special provisions	149, B52, IB2, T4, TP1, TP8, TP28
Packaging exceptions	150
Packaging non bulk	173
Packaging bulk	242

IATA	
UN number	UN1263
UN proper shipping name	Paint (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base)
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Packing group	II
Environmental hazards	Yes
ERG Code	3L
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo aircraft Allowed.
Cargo aircraft only Allowed.

IMDG

UN number UN1263
UN proper shipping name PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound)

Transport hazard class(es)

Class 3

Subsidiary risk -

Packing group II

Environmental hazards

Marine pollutant Yes

EmS F-E, S-E

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not established.

DOT



IATA; IMDG



Marine pollutant



General information IMDG Regulated Marine Pollutant.

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

PCBTF, P-Chlorobenzotrifluoride (CAS 98-56-6) 1.0 % One-Time Export Notification only.

CERCLA Hazardous Substance List (40 CFR 302.4)

ACETONE (CAS 67-64-1) Listed.
 DIMETHYLBENZENE (MIXED ISOMERS) (CAS 1330-20-7) Listed.
 ETHYLBENZENE (CAS 100-41-4) Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes
 Delayed Hazard - Yes
 Fire Hazard - Yes
 Pressure Hazard - No
 Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical No

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
DIMETHYLBENZENE (MIXED ISOMERS)	1330-20-7	3 - < 5
ETHYLBENZENE	100-41-4	< 1

Other federal regulations**Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

DIMETHYLBENZENE (MIXED ISOMERS) (CAS 1330-20-7)
 ETHYLBENZENE (CAS 100-41-4)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Not regulated.

Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number

ACETONE (CAS 67-64-1) 6532

Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

ACETONE (CAS 67-64-1) 35 %WV

DEA Exempt Chemical Mixtures Code Number

ACETONE (CAS 67-64-1) 6532

US state regulations**US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)**

Not listed.

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

ACETONE (CAS 67-64-1)
 CARBON BLACK (CAS 1333-86-4)
 DIMETHYLBENZENE (MIXED ISOMERS) (CAS 1330-20-7)
 ETHYLBENZENE (CAS 100-41-4)
 MINERAL SPIRITS (CAS 64742-88-7)
 SOLVENT NAPHTHA (PETROLEUM), LIGHT AROMATIC (CAS 64742-95-6)
 TRIMETHYLBENZENE (CAS 25551-13-7)

US. Massachusetts RTK - Substance List

ACETONE (CAS 67-64-1)
 CARBON BLACK (CAS 1333-86-4)
 DIMETHYLBENZENE (MIXED ISOMERS) (CAS 1330-20-7)
 ETHYLBENZENE (CAS 100-41-4)
 MINERAL SPIRITS (CAS 64742-88-7)
 SILICON DIOXIDE (CAS 112926-00-8)
 TRIMETHYLBENZENE (CAS 25551-13-7)

US. New Jersey Worker and Community Right-to-Know Act

ACETONE (CAS 67-64-1)
CARBON BLACK (CAS 1333-86-4)
DIMETHYLBENZENE (MIXED ISOMERS) (CAS 1330-20-7)
ETHYLBENZENE (CAS 100-41-4)
MINERAL SPIRITS (CAS 64742-88-7)
PCBTF, P-Chlorobenzotrifluoride (CAS 98-56-6)
SILICON DIOXIDE (CAS 112926-00-8)
TRIMETHYLBENZENE (CAS 25551-13-7)

US. Pennsylvania Worker and Community Right-to-Know Law

ACETONE (CAS 67-64-1)
CARBON BLACK (CAS 1333-86-4)
DIMETHYLBENZENE (MIXED ISOMERS) (CAS 1330-20-7)
ETHYLBENZENE (CAS 100-41-4)
MINERAL SPIRITS (CAS 64742-88-7)
TRIMETHYLBENZENE (CAS 25551-13-7)

US. Rhode Island RTK

ACETONE (CAS 67-64-1)
DIMETHYLBENZENE (MIXED ISOMERS) (CAS 1330-20-7)
ETHYLBENZENE (CAS 100-41-4)

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

BENZENE (CAS 71-43-2)	Listed: February 27, 1987
CARBON BLACK (CAS 1333-86-4)	Listed: February 21, 2003
CRYSTALLINE SILICA QUARTZ (CAS 14808-60-7)	Listed: October 1, 1988
CUMENE (CAS 98-82-8)	Listed: April 6, 2010
ETHYLBENZENE (CAS 100-41-4)	Listed: June 11, 2004
NAPHTHALENE (CAS 91-20-3)	Listed: April 19, 2002
TITANIUM DIOXIDE (CAS 13463-67-7)	Listed: September 2, 2011

US - California Proposition 65 - CRT: Listed date/Developmental toxin

BENZENE (CAS 71-43-2)	Listed: December 26, 1997
TOLUENE (CAS 108-88-3)	Listed: January 1, 1991

US - California Proposition 65 - CRT: Listed date/Female reproductive toxin

TOLUENE (CAS 108-88-3)	Listed: August 7, 2009
------------------------	------------------------

US - California Proposition 65 - CRT: Listed date/Male reproductive toxin

BENZENE (CAS 71-43-2)	Listed: December 26, 1997
-----------------------	---------------------------

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	11-19-2015
Version #	01
HMIS® ratings	Health: 2* Flammability: 3 Physical hazard: 0
NFPA ratings	Health: 2 Flammability: 3 Instability: 0

NFPA ratings



Disclaimer

The information contained herein is based on data supplied to us from sources believed to be reliable at the date of issue. Nothing herein shall be deemed to create any warranty of any kind, express or implied, concerning the accuracy or completeness of the information provided or the results to be obtained from the use thereof. It is offered for your consideration, investigation and verification. Buyer assumes all risk of use, storage, transportation, handling and disposal of the product in compliance with applicable federal, state and local laws and regulations. This information relates to the material designated and may not be valid for such material used in combination with any other materials nor in any process.